

POTABLE DRINKING **WATER TRAILER**



Trailer is not NSF Certified, but all plumbing components are.	
Capacity	550 Gallons (FDA & NSF Approved/
	Polyethylene Tank w/lid lock)
Pump	2" Stainless Steel with Honda
•	(NSF/ANSI 61 & 372 Certified)
Maximum Flow Rate	180 Gallons Per Minute
Hoses & Plumbing	All Hoses Are Food Grade.
	All Plumbing Is Compatible With
	Potable Drinking Water.
Fill	2" Anti-Siphon with 20' of 2" Hose
Garden Hose Spigots	1 Gravity and 1 Pressure
Hitch	2" Ball or 3" Pintle
Trailer	DOT Approved with Surge Brakes
Axles / Brakes	Tandem Spring Axles / Surge
	Brakes
Tires	ST225/75D15
GVWR	6,000 lb
Empty Weight	1,800 lb
Length X Width X Height	L 161" X W 79" X H 66"
Options	Hose Reel with 1" X 50' Hose
·	









POTABLE DRINKING WATER TRAILER (GRAVITY FLOW)



Specifications	
Capacity	550 Gallons (FDA Approved & NSF/ ANSI Certified Poly Tank w/lid lock)
Discharge	Gravity Flow
Number of Outlets	3 Garden Hose Spigots/1 - 2" Valve
Fill	2" Anti-Siphon with 20' of 2" Hose
Hitch	2" Ball Adjustable Height
Trailer	DOT Approved
Frame	6" Channel Iron
Axles/Brakes	Tandem Spring/Surge
Tires	ST225/75D15
GVWR	6,000 lb
Empty Weight	1,800 lb

Our potable water trailers are designed for the sole purpose of transporting and distributing drinking water. From the food grade hoses, to the anti-algae black tank, these water trailers are perfect anytime to need to deliver clean, consumable water.



