

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	8 Degrees			15 Degrees			28 Degrees		
			Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)
280	70	280	39.2	225.0	2.4	40.8	222.3	2.7			
280	90	70	80.9	373.4	13.8 *						
280	90	80	79.3	371.4	13.5 *	81.6	369.3	12.4 *			
280	90	90	77.7	369.2	13.3 *	80.0	367.0	12.1 *			
280	90	100	76.1	366.6	13.1 *	78.4	364.5	11.7 *	80.6	360.2	11.1 *
280	90	110	74.5	363.8	12.8 *	76.8	361.6	11.4 *	79.0	357.3	10.4 *
280	90	120	72.9	360.6	12.6 *	75.2	358.5	10.8 *	77.3	354.1	9.7 *
280	90	130	71.3	357.2	11.8 *	73.6	355.0	9.7 *	75.7	350.6	7.2 *
280	90	140	69.6	353.4	11.0 *	71.9	351.2	8.8 *	74.0	346.7	6.4 *
280	90	150	68.0	349.3	10.1 *	70.2	347.0	8.0 *	72.3	342.5	5.7 *
280	90	160	66.3	344.8	9.3 *	68.5	342.5	7.3 *	70.6	338.0	5.1 *
280	90	170	64.6	340.0	8.5 *	66.8	337.6	6.7 *	68.8	333.0	4.6 *
280	90	180	62.8	334.8	7.8 *	65.1	332.4	6.1 *	67.1	327.7	4.2 *
280	90	190	61.1	329.2	7.2 *	63.3	326.8	5.6 *	65.3	322.0	3.9 *
280	90	200	59.3	323.1	6.7 *	61.5	320.7	5.2 *	63.4	315.8	3.5 *
280	90	210	57.4	316.7	6.1 *	59.6	314.2	4.7 *	61.6	309.2	3.2 *
280	90	220	55.6	309.8	5.7 *	57.7	307.2	4.4 *	59.6	302.1	2.9 *
280	90	230	53.7	302.3	5.3 *	55.8	299.7	4.1 *	57.7	294.5	2.6 *
280	90	240	51.7	294.4	5.0 *	53.8	291.7	3.7 *	55.6	286.3	2.4 *
280	90	250	49.7	285.8	4.6 *	51.8	283.0	3.5 *	53.6	277.5	2.2 *
280	90	260	47.6	276.6	4.2 *	49.7	273.7	3.2 *	51.4	268.0	2.0 *
280	90	270	45.4	266.7	3.5 *	47.5	263.7	2.9 *			
280	90	280	43.1	256.0	2.8 *	45.2	252.9	2.7 *			
280	90	290	40.8	244.4	2.2 *	42.8	241.1	2.6 *			

28p1131

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	5 Degrees				15 Degrees				25 Degrees			
			Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)
280	30	220	46.5	232.1	6.2	47.3	230.9	6.5	47.9	228.7	6.6	45.3	218.4	5.6
280	30	230	43.9	222.9	5.3	44.7	220.8	5.4	44.9	209.8	4.8	43.3	208.7	5.6
280	30	240	41.2	210.9	4.4	41.9	209.8	3.7	39.0	197.3	3.7	35.8	183.5	2.9
280	30	250	38.3	198.8	3.5	38.3	197.3	2.1	35.8	183.5	2.1	32.0	170.2	2.1
280	30	270	31.8	169.6	2.1	31.8	169.6	1.1	28.0	147.3	1.1	24.1	134.4	1.1
280	50	60	80.9	334.7	30.8	80.9	331.4	28.6	78.8	329.2	26.3	76.8	326.7	24.1
280	50	70	77.4	332.8	28.4	77.4	329.2	26.3	75.2	326.7	24.1	73.0	323.8	21.9
280	50	80	73.8	330.5	26.2	73.8	323.8	24.1	71.6	320.5	21.9	69.4	317.0	19.3
280	50	90	70.2	328.1	24.1	70.2	320.5	20.2	67.8	313.0	18.3	65.6	308.6	16.8
280	50	100	66.4	314.4	18.7	66.4	308.6	16.8	64.0	303.9	14.0	61.1	298.7	12.8
280	50	110	62.6	305.3	15.8	62.6	298.7	14.0	60.0	293.1	11.9	57.9	287.1	10.9
280	50	120	58.6	294.6	13.5	58.6	287.1	11.9	55.7	280.5	10.1	53.6	273.4	9.3
280	50	130	54.4	282.0	12.0	54.4	280.5	10.1	51.3	265.7	8.3	49.0	257.3	7.2
280	50	140	50.0	267.3	10.5	50.0	265.7	8.3	46.6	248.3	6.2	44.0	238.5	5.2
280	50	150	47.7	259.0	9.1	47.7	265.7	7.2	43.3	235.5	5.2	40.6	227.8	4.4
280	50	160	45.3	250.1	8.8	45.3	257.3	6.2	41.3	227.8	4.4	38.5	216.0	3.6
280	50	170	42.8	240.3	7.9	42.8	253.6	5.2	35.5	203.1	2.8	32.0	188.7	2.2
280	50	180	40.1	229.7	6.8	40.1	248.3	4.4	28.0	170.2	1.1	24.1	157.3	1.1
280	50	190	37.3	218.1	5.8	37.3	243.3	3.6	24.1	157.3	1.1	20.4	143.3	1.1
280	50	200	34.3	205.3	4.9	34.3	238.5	2.8	20.4	143.3	1.1	18.8	130.0	1.1
280	50	210	31.8	191.0	4.1	31.8	233.5	2.2	18.8	130.0	1.1	17.2	117.3	1.1
280	50	220	29.3	176.7	3.3	29.3	228.5	1.9	17.2	117.3	1.1	15.7	104.0	1.1
280	50	230	26.8	162.4	2.6	26.8	223.5	1.5	15.7	104.0	1.1	14.3	90.7	1.1
280	50	240	24.3	148.1	2.0	24.3	218.5	1.1	14.3	90.7	1.1	13.0	77.4	1.1
280	50	250	21.8	133.8	1.5	21.8	213.5	0.8	13.0	77.4	1.1	11.9	64.0	1.1
280	50	260	19.3	119.5	1.1	19.3	208.5	0.6	11.9	64.0	1.1	10.9	50.0	1.1
280	50	270	16.8	105.2	0.8	16.8	203.5	0.4	10.9	50.0	1.1	9.3	35.8	1.1
280	50	280	14.3	90.9	0.6	14.3	198.5	0.3	9.3	35.8	1.1	8.3	21.8	1.1
280	50	290	11.8	76.6	0.4	11.8	193.5	0.2	8.3	21.8	1.1	7.6	7.3	1.1
280	50	300	9.3	62.3	0.3	9.3	188.5	0.1	7.6	7.3	1.1	6.4	0.0	1.1
280	50	310	6.8	48.0	0.2	6.8	183.5	0.1	6.4	0.0	1.1	6.0	0.0	1.1
280	50	320	4.3	33.7	0.1	4.3	178.5	0.1	6.0	0.0	1.1	5.8	0.0	1.1
280	50	330	1.8	19.4	0.0	1.8	173.5	0.0	5.8	0.0	1.1	5.4	0.0	1.1
280	50	340	0.0	5.1	0.0	0.0	168.5	0.0	5.4	0.0	1.1	5.1	0.0	1.1
280	50	350	0.0	0.0	0.0	0.0	163.5	0.0	5.1	0.0	1.1	4.8	0.0	1.1
280	50	360	0.0	0.0	0.0	0.0	158.5	0.0	4.8	0.0	1.1	4.5	0.0	1.1
280	50	370	0.0	0.0	0.0	0.0	153.5	0.0	4.5	0.0	1.1	4.2	0.0	1.1
280	50	380	0.0	0.0	0.0	0.0	148.5	0.0	4.2	0.0	1.1	3.9	0.0	1.1
280	50	390	0.0	0.0	0.0	0.0	143.5	0.0	3.9	0.0	1.1	3.6	0.0	1.1
280	50	400	0.0	0.0	0.0	0.0	138.5	0.0	3.6	0.0	1.1	3.4	0.0	1.1
280	50	410	0.0	0.0	0.0	0.0	133.5	0.0	3.4	0.0	1.1	3.1	0.0	1.1
280	50	420	0.0	0.0	0.0	0.0	128.5	0.0	3.1	0.0	1.1	2.8	0.0	1.1
280	50	430	0.0	0.0	0.0	0.0	123.5	0.0	2.8	0.0	1.1	2.5	0.0	1.1
280	50	440	0.0	0.0	0.0	0.0	118.5	0.0	2.5	0.0	1.1	2.2	0.0	1.1
280	50	450	0.0	0.0	0.0	0.0	113.5	0.0	2.2	0.0	1.1	1.9	0.0	1.1
280	50	460	0.0	0.0	0.0	0.0	108.5	0.0	1.9	0.0	1.1	1.6	0.0	1.1
280	50	470	0.0	0.0	0.0	0.0	103.5	0.0	1.6	0.0	1.1	1.3	0.0	1.1
280	50	480	0.0	0.0	0.0	0.0	98.5	0.0	1.3	0.0	1.1	1.0	0.0	1.1
280	50	490	0.0	0.0	0.0	0.0	93.5	0.0	1.0	0.0	1.1	0.7	0.0	1.1
280	50	500	0.0	0.0	0.0	0.0	88.5	0.0	0.7	0.0	1.1	0.4	0.0	1.1
280	50	510	0.0	0.0	0.0	0.0	83.5	0.0	0.4	0.0	1.1	0.1	0.0	1.1
280	50	520	0.0	0.0	0.0	0.0	78.5	0.0	0.1	0.0	1.1	0.0	0.0	1.1
280	50	530	0.0	0.0	0.0	0.0	73.5	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	540	0.0	0.0	0.0	0.0	68.5	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	550	0.0	0.0	0.0	0.0	63.5	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	560	0.0	0.0	0.0	0.0	58.5	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	570	0.0	0.0	0.0	0.0	53.5	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	580	0.0	0.0	0.0	0.0	48.5	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	590	0.0	0.0	0.0	0.0	43.5	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	600	0.0	0.0	0.0	0.0	38.5	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	610	0.0	0.0	0.0	0.0	33.5	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	620	0.0	0.0	0.0	0.0	28.5	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	630	0.0	0.0	0.0	0.0	23.5	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	640	0.0	0.0	0.0	0.0	18.5	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	650	0.0	0.0	0.0	0.0	13.5	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	660	0.0	0.0	0.0	0.0	8.5	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	670	0.0	0.0	0.0	0.0	3.5	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	680	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	690	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	700	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	710	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	720	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	730	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	740	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	750	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	760	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	770	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	780	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	790	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	800	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	810	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	820	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	830	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	840	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	850	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	860	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	870	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	880	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	890	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	900	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	910	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	920	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	930	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.1	0.0	0.0	1.1
280	50	940	0.0	0.0										

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	5 Degrees			15 Degrees			55 Degrees		
			Boom Angle (deg)	Jib Pt Height (ft)	AB-A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB-A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB-A Capacity (1000 lbs)
270	70	200	55.8	287.2	9.2 *	57.7	285.2	7.4 *	59.3	281.0	5.4 *
270	70	210	53.8	279.5	8.5 *	55.6	277.8	6.4 *	57.2	274.8	4.8 *
270	70	220	51.7	272.0	7.7	53.5	269.8	5.4 *	55.0	267.4	4.2 *
270	70	230	49.5	263.5	6.7	51.3	261.3	4.4 *	52.8	258.7	3.6 *
270	70	240	47.2	254.3	5.8	49.0	252.0	3.4 *	50.4	247.3	3.0 *
270	70	250	44.9	244.3	4.9	46.8	241.9	2.4 *	48.0	237.0	2.4 *
270	70	260	42.4	233.4	4.2	44.1	230.9	1.4 *	45.4	225.7	1.8 *
270	70	270	39.8	221.5	3.5	41.5	218.8	0.4 *	42.8	210.4	1.2 *
270	70	280	37.0	208.5	2.8	38.7	205.6	0.4 *	40.2	205.6	0.6 *
270	70	290	34.1	193.9	2.2	35.7	190.8	0.4 *	37.6	190.8	0.0 *
270	90	70	80.6	363.2	13.7 *	81.4	359.1	12.3 *	80.4	349.9	10.3 *
270	90	80	79.0	361.2	13.5 *	79.8	356.8	12.0 *	78.7	346.9	9.3 *
270	90	90	77.4	358.9	13.3 *	78.1	354.1	11.7 *	77.0	343.6	8.2 *
270	90	100	75.7	356.3	13.0 *	76.5	351.2	11.3 *	75.3	340.0	7.4 *
270	90	110	74.1	353.3	12.8 *	74.8	347.9	11.0 *	73.5	336.0	6.6 *
270	90	120	72.4	350.1	12.5 *	73.1	344.3	10.2 *	71.8	331.6	6.0 *
270	90	130	70.7	346.5	12.2 *	71.4	340.4	9.3 *	70.0	326.9	5.4 *
270	90	140	69.0	342.6	11.4 *	69.6	336.1	8.5 *	68.2	321.8	4.9 *
270	90	150	67.3	338.4	10.4 *	67.9	331.5	7.7 *	66.4	316.3	4.4 *
270	90	160	65.6	333.7	9.8 *	66.1	326.4	7.1 *	64.5	310.4	4.0 *
270	90	170	63.8	328.7	9.0 *	64.3	321.0	6.5 *	62.6	304.0	3.6 *
270	90	180	62.0	323.3	8.2 *	62.5	315.1	5.9 *	60.6	297.1	3.3 *
270	90	190	60.2	317.5	7.7 *	60.6	308.8	5.4 *	58.6	289.7	3.0 *
270	90	200	58.3	311.3	7.1 *	58.7	302.1	5.0 *	56.6	281.7	2.8 *
270	90	210	56.4	304.6	6.5 *	56.7	294.8	4.6 *	54.4	273.1	2.5 *
270	90	220	54.5	297.4	6.0 *	54.7	287.0	4.3 *	52.2	263.9	2.3 *
270	90	230	52.5	289.6	5.6 *	52.6	278.6	3.9 *	50.0	253.8	2.2 *
270	90	240	50.4	281.3	5.3 *	50.4	269.5	3.6 *	47.6	243.0	2.0 *
270	90	250	48.3	272.3	4.8 *	48.2	259.7	3.3 *			
270	90	260	46.1	262.6	4.5 *	45.9	249.1	3.1 *			
270	90	270	43.8	252.2	3.8	43.5	237.6	2.9 *			
270	90	280	41.4	240.8	3.2	40.9	225.0	2.8 *			
270	90	290	38.9	228.4	2.6	38.2	211.2	2.3			
270	90	300	36.2	214.8	2.0						
280	30	50	81.9	316.1	40.0 *	80.9	313.6	40.0 *	81.8	311.9	35.3 *
280	30	60	80.0	314.4	40.0 *	79.0	311.5	34.7 *	79.9	309.9	32.2 *
280	30	70	78.1	312.4	39.0 *	77.1	309.2	31.8 *	78.0	307.5	29.4 *
280	30	80	76.2	310.0	33.6 *	75.2	306.4	29.2 *	76.1	304.7	26.9 *
280	30	90	74.3	307.3	30.6 *	73.3	303.4	27.0 *	74.1	301.6	24.8 *
280	30	100	72.4	304.2	28.4 *	71.4	299.9	24.7 *	72.2	298.2	22.6 *
280	30	110	70.5	300.8	26.1 *	69.4	296.0	22.5 *	70.2	294.3	20.8 *
280	30	120	68.5	296.9	24.0 *	67.4	291.8	21.0 *	68.2	290.0	19.1 *
280	30	130	66.5	292.7	22.0 *	65.4	287.1	19.2 *	66.1	285.3	17.5 *
280	30	140	64.5	288.0	19.8	63.3	282.0	17.6	64.1	280.2	16.0 *
280	30	150	62.4	282.9	17.2	61.2	276.4	15.4	61.9	274.5	14.7 *
280	30	160	60.3	277.4	15.0	59.0	270.3	13.4	59.8	268.4	13.5 *
280	30	170	58.2	271.3	13.1	56.8	263.7	11.7	57.5	261.7	12.0
280	30	180	56.0	264.7	11.4	54.6	256.5	10.2	55.3	254.5	10.4
280	30	190	53.7	257.6	9.9	52.2	248.7	8.8	52.9	246.6	9.0
280	30	200	51.4	249.8	8.5	49.8	240.2	7.6	50.5	238.0	7.7
280	30	210	49.0	241.3	7.3						

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	8 Degrees			14 Degrees			25 Degrees		
			Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)
270	30	180	83.6	278.9	20.1	64.5	275.9	20.6	65.3	274.1	18.6 *
270	30	180	81.8	271.8	17.6	62.3	270.6	18.0	63.1	268.8	17.1 *
270	30	180	80.2	265.7	15.4	60.1	264.8	15.7	60.9	262.9	15.8 *
270	30	180	57.0	258.4	13.5	57.9	258.4	12.1	56.6	256.5	14.1
270	30	180	54.7	252.5	11.8	55.6	251.5	10.5	53.9	249.5	12.3
270	30	200	48.9	245.0	8.9	53.2	243.9	9.2	51.4	241.9	10.7
270	30	220	44.7	236.7	7.7	50.7	235.7	8.8	48.8	233.5	9.4
270	30	240	41.9	227.8	6.6	48.2	226.7	7.9	46.1	224.4	8.1
270	30	260	38.6	207.1	4.7	45.5	216.8	6.8		214.4	7.0
270	30	280	35.8	185.2	3.9	42.7	205.9	5.8			
270	30	300	32.3	166.8	3.2	39.7	193.9	5.0			
270	30	320	28.5	149.4	2.5	36.5	180.4	4.0			
270	50	60	80.6	324.5	32.0 *	80.3	321.2	30.1 *	81.7	318.6	27.1 *
270	50	70	78.8	322.5	31.5 *	78.5	318.9	27.9 *	79.8	316.3	24.6 *
270	50	80	77.0	320.3	29.7 *	76.6	316.3	25.6 *	78.0	313.7	22.1 *
270	50	90	75.1	317.6	27.9 *	74.8	313.3	23.2 *	76.1	310.6	19.9 *
270	50	100	73.3	314.7	25.8 *	72.9	310.0	21.4 *	74.2	307.3	18.0 *
270	50	110	71.4	311.3	23.8 *	71.0	306.2	19.6 *	72.3	303.5	16.5 *
270	50	120	69.5	307.6	21.9 *	69.0	302.1	17.9 *	70.3	299.4	15.0 *
270	50	130	67.6	303.5	20.0 *	67.1	297.6	16.3 *	68.4	294.8	13.6 *
270	50	140	65.6	299.1	18.4 *	65.1	292.7	15.1 *	66.3	289.9	12.2 *
270	50	150	63.7	294.2	17.0 *	63.1	287.3	13.9 *	64.3	284.4	11.3 *
270	50	160	61.7	288.8	15.7 *	61.0	281.5	12.7 *	62.2	278.5	10.3 *
270	50	170	59.6	283.0	14.1	58.9	275.2	11.6 *	60.1	272.1	9.4 *
270	50	180	57.5	276.7	12.4	56.7	268.3	10.8 *	57.9	265.2	8.6 *
270	50	190	55.3	269.9	10.9	54.5	260.8	9.9	55.6	257.6	7.9 *
270	50	200	53.1	262.5	9.5	52.2	252.7	8.7	53.3	249.4	7.3 *
270	50	210	50.8	254.4	8.3	49.8	244.0	7.5	50.9	240.5	6.8 *
270	50	220	48.5	245.7	7.2	47.3	234.4	6.5	48.4	230.8	6.3 *
270	50	230	46.0	236.2	6.2	44.8	223.9	5.6	45.8	220.2	5.8
270	50	240	43.5	225.8	5.3	42.0	212.5	4.7			
270	50	250	40.8	214.5	4.5	39.2	199.8	3.9			
270	50	260	37.9	201.9	3.7	36.1	185.7	3.2			
270	50	280	34.9	188.0	3.0						
270	50	300	31.6	172.3	2.4						
270	70	60	81.5	344.7	21.9 *	81.9	335.6	18.1 *			
270	70	70	79.8	342.9	21.6 *	80.1	333.1	16.3 *			
270	70	80	78.0	340.8	21.4 *	78.3	330.2	14.6 *			
270	70	90	76.3	338.3	21.1 *	76.6	327.1	13.2 *			
270	70	100	74.6	335.5	20.1 *	74.8	323.6	11.9 *			
270	70	110	72.8	332.4	18.9 *	72.9	319.7	10.5 *			
270	70	120	71.1	328.9	17.6 *	71.1	315.4	9.6 *			
270	70	130	69.3	325.1	16.1 *	69.2	310.8	8.6 *			
270	70	140	67.5	320.9	14.8 *	67.3	305.8	7.8 *			
270	70	150	65.6	316.4	13.6 *	65.4	300.3	7.1 *			
270	70	160	63.7	311.4	12.6 *	63.4	294.4	6.5 *			
270	70	170	61.8	306.1	11.7 *	61.4	288.0	5.9 *			
270	70	180	59.9	300.3	10.7 *						
270	70	190	57.9	294.0	9.8 *						

Refer to all notes in front of the Crane Rating Manual before operating the machine.											
Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	Jib Angle to Boom								
			5 Degrees			15 Degrees			25 Degrees		
			Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)
260	70	140	66.7	310.0	15.7 *	66.7	308.2	13.2 *	70.5	304.5	9.9 *
260	70	150	64.8	305.3	14.5 *	64.8	303.4	12.1 *	68.5	298.7	8.9 *
260	70	160	62.9	300.1	13.3 *	62.9	298.2	11.1 *	66.5	293.4	8.1 *
260	70	170	60.9	294.6	12.3 *	60.9	292.6	10.1 *	64.5	288.1	7.4 *
260	70	180	58.9	288.5	11.5 *	58.9	286.5	9.4 *	62.5	282.6	6.7 *
260	70	190	56.8	282.0	10.6 *	56.7	280.0	8.5 *	60.4	276.9	6.1 *
260	70	200	54.7	274.9	9.9 *	54.6	272.8	7.9 *	58.2	270.7	5.6 *
260	70	210	52.5	267.3	9.2 *	54.4	265.1	7.3 *	56.0	264.0	5.2 *
260	70	220	50.3	259.0	8.1 *	52.1	256.8	6.8 *	53.7	257.3	4.8 *
260	70	230	48.0	250.0	7.1 *	49.8	247.7	6.2 *	51.3	243.1	4.4 *
260	70	240	45.6	240.3	6.1 *	47.4	237.9	5.5 *	48.8	233.1	4.1 *
260	70	250	43.1	229.6	5.3 *	44.8	227.1	5.5 *	46.2	222.1	3.7 *
260	70	260	40.4	218.0	4.5 *	42.2	215.3	4.9 *			
260	70	270	37.6	205.2	3.8 *	39.3	202.4	4.1 *			
260	70	280	34.6	190.9	3.2 *	36.3	187.9	3.4 *			
260	70	290	31.3	174.9	2.6 *						
260	70	300	27.7	156.5	2.0 *						
260	90	60	82.0	354.8	13.9 *						
260	90	70	80.3	353.1	13.7 *						
260	90	80	78.7	351.0	13.5 *	81.1	348.9	12.3 *	81.8	342.3	10.4 *
260	90	90	77.0	348.6	13.2 *	79.5	346.5	11.9 *	80.1	339.6	10.3 *
260	90	100	75.3	345.9	12.9 *	77.8	343.8	11.6 *	78.3	336.5	9.7 *
260	90	110	73.6	342.9	12.7 *	76.0	340.7	11.3 *	76.8	333.1	8.6 *
260	90	120	71.9	339.5	12.4 *	74.3	337.4	10.9 *	74.8	329.3	7.7 *
260	90	130	70.2	335.8	12.1 *	72.6	333.6	10.5 *	73.0	325.2	6.9 *
260	90	140	68.4	331.8	11.7 *	70.8	329.6	9.6 *	71.2	320.7	6.3 *
260	90	150	66.6	327.4	11.0 *	69.0	325.1	8.8 *	69.4	315.8	5.7 *
260	90	160	64.8	322.6	10.1 *	67.2	320.3	8.0 *	67.5	310.5	5.1 *
260	90	170	63.0	317.4	9.3 *	65.4	315.1	7.2 *	65.6	304.8	4.5 *
260	90	180	61.1	311.8	8.7 *	63.5	309.5	6.6 *	63.6	298.6	4.1 *
260	90	190	59.2	305.8	8.0 *	61.6	303.4	6.1 *	61.6	291.9	3.8 *
260	90	200	57.3	299.3	7.4 *	59.6	296.9	5.7 *	59.6	284.8	3.4 *
260	90	210	55.3	292.3	6.8 *	57.6	289.8	5.3 *	57.5	277.0	3.2 *
260	90	220	53.3	284.8	6.4 *	55.5	282.2	4.8 *	55.4	268.7	2.9 *
260	90	230	51.2	276.7	5.9 *	53.4	274.0	4.5 *	53.1	259.6	2.7 *
260	90	240	49.0	267.9	5.5 *	51.2	265.2	4.2 *	50.8	249.9	2.4 *
260	90	250	46.8	258.5	5.2 *	49.0	255.6	3.8 *	48.4	239.3	2.3 *
260	90	260	44.4	248.2	4.8 *	46.6	245.3	3.6 *	45.9	227.7	2.1 *
260	90	270	42.0	237.1	4.2 *	44.2	234.0	3.3 *			
260	90	280	39.5	225.0	3.6 *	41.6	221.7	3.1 *			
260	90	290	36.7	211.6	3.0 *	38.8	208.1	2.9 *			
260	90	300	33.8	196.8	2.4 *	35.8	193.0	2.7 *			
270	30	50	81.6	306.0	40.0 *	80.6	303.4	40.0 *	81.5	301.7	40.0 *
270	30	60	79.7	304.2	40.0 *	78.7	301.3	39.9 *	79.5	299.6	34.7 *
270	30	70	77.7	302.1	40.0 *	76.7	298.8	34.0 *	77.6	297.2	31.7 *
270	30	80	75.8	299.7	38.4 *	74.7	296.0	31.5 *	75.6	294.3	28.9 *
270	30	90	73.8	296.9	33.3 *	72.7	292.8	29.0 *	73.6	291.1	26.5 *
270	30	100	71.8	293.7	30.4 *	70.7	289.2	26.5 *	71.6	287.5	24.4 *
270	30	110	69.8	290.1	27.9 *	68.7	285.2	24.6 *	69.5	283.5	22.4 *
270	30	120	67.8	286.1	25.8 *	66.6	280.8	22.5 *	67.4	279.0	20.6 *
270	30	130	65.7	281.7	23.1 *						

28p1131

29 of 33

1/2

C-268

Select

Convent Boom

Luffing Boom

Jib Section

Load

28p1131

Select
↓
Convent
Boom
Luffing Boom
Jib Erection

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	5 Degrees				15 Degrees				25 Degrees			
			Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)			
260	30	70	77.3	291.9	40.0 *	76.3	291.0	40.0 *	75.2	289.4	39.8 *			
260	30	80	75.3	289.3	40.0 *	74.2	288.5	39.4 *	73.1	286.9	38.6 *			
260	30	90	73.2	286.4	40.0 *	72.1	285.6	38.8 *	71.0	284.0	38.0 *			
260	30	100	71.2	283.1	37.6 *	70.0	282.2	38.3 *	68.9	280.6	37.4 *			
260	30	110	69.1	279.4	33.0 *	67.9	278.5	37.4 *	66.8	276.9	36.5 *			
260	30	120	67.0	275.2	30.2 *	65.7	274.4	36.8 *	64.6	272.7	35.8 *			
260	30	130	64.8	270.7	27.0	63.5	269.8	36.2 *	62.4	268.1	35.2 *			
260	30	140	62.6	265.6	23.5	61.3	264.7	35.6 *	60.2	262.4	34.6 *			
260	30	150	60.4	260.1	20.5	59.0	259.1	35.0 *	57.9	257.5	33.8 *			
260	30	160	58.1	254.0	17.9	56.8	253.0	34.4 *	55.7	251.2	33.2 *			
260	30	170	55.7	247.3	15.7	54.6	246.3	33.8 *	53.5	239.0	32.6 *			
260	30	180	53.3	240.1	13.8	52.4	239.0	33.2 *	51.3	231.0	32.0 *			
260	30	190	50.8	232.1	12.1	50.2	230.0	32.6 *	49.1	222.3	31.4 *			
260	30	200	48.2	223.4	10.6	48.0	222.3	30.8 *	46.9	214.7	30.6 *			
260	30	210	45.5	213.9	9.3	46.9	212.7	30.2 *	45.8	206.1	29.8 *			
260	30	220	42.6	203.3	8.1	44.7	202.1	29.2 *	43.6	194.4	29.2 *			
260	30	230	39.6	191.7	7.0	42.5	190.4	28.6 *	41.4	182.2	28.6 *			
260	30	240	36.4	178.6	6.0	40.3	177.2	28.0 *	39.2	172.2	28.0 *			
260	30	250	32.9	163.9	5.1	37.2	170.4	27.4 *	36.1	164.4	27.4 *			
260	30	260	29.0	146.9	4.3	35.0	157.2	26.8 *	34.0	154.4	26.8 *			
260	50	60	80.3	314.3	32.0 *	81.9	313.0	31.9 *	80.8	311.0	31.8 *			
260	50	70	78.4	312.3	32.0 *	80.0	311.0	31.8 *	78.9	308.6	31.7 *			
260	50	80	76.6	309.9	30.3 *	78.1	308.6	30.8 *	77.0	306.6	31.6 *			
260	50	90	74.7	307.2	28.5 *	76.2	305.9	29.9 *	75.1	303.9	29.8 *			
260	50	100	72.7	304.2	26.8 *	74.2	302.8	27.2 *	73.1	301.9	27.1 *			
260	50	110	70.8	300.7	25.2 *	72.3	299.3	25.0 *	71.2	297.9	24.9 *			
260	50	120	68.8	296.9	23.2 *	70.3	295.5	22.9 *	69.2	294.5	22.8 *			
260	50	130	66.8	292.6	21.4 *	68.3	291.2	20.8 *	67.2	290.2	20.7 *			
260	50	140	64.8	288.0	19.8 *	66.3	286.6	19.1 *	65.2	285.2	19.0 *			
260	50	150	62.8	282.9	18.3 *	64.2	281.4	17.6 *	63.1	279.8	17.5 *			
260	50	160	60.7	277.3	16.4	62.1	275.8	16.1 *	61.0	274.2	16.0 *			
260	50	170	58.5	271.2	14.4	59.9	269.7	14.8 *	58.8	267.6	14.7 *			
260	50	180	56.3	264.7	12.7	57.7	263.1	13.5 *	56.6	261.6	13.4 *			
260	50	190	54.0	257.5	11.2	55.5	255.9	12.6 *	54.4	254.1	12.5 *			
260	50	200	51.7	249.7	9.9	53.1	248.1	11.7	52.0	246.1	11.6 *			
260	50	210	49.3	241.2	8.7	50.7	239.5	10.3	49.6	237.5	10.2 *			
260	50	220	46.8	232.0	7.6	48.2	230.2	9.0	47.1	228.5	8.9 *			
260	50	230	44.2	221.9	6.6	45.5	220.0	7.9	44.4	221.9	7.8 *			
260	50	240	41.5	210.8	5.7	42.8	208.8	6.9	41.7	210.8	6.8 *			
260	50	250	38.6	198.5	4.9	39.9	196.5	5.9	38.8	200.8	5.8 *			
260	50	260	35.5	184.9	4.1	36.7	182.6	5.1	35.6	190.4	5.0 *			
260	50	270	32.1	169.5	3.4	33.6	170.4	4.3	32.5	178.2	4.2 *			
260	50	280	28.4	151.7	2.7	30.5	157.2	3.5	29.4	166.0	3.4 *			
70	60	81.2	334.6	21.8 *	81.5	331.0	20.3 *	81.6	325.3	18.4 *	81.7	319.6	16.5 *	
70	70	79.4	332.7	21.6 *	79.7	328.8	20.0 *	79.8	322.8	16.9 *	79.9	317.1	14.6 *	
70	80	77.7	330.5	21.3 *	77.9	326.2	19.6 *	78.0	316.6	15.2 *	78.1	311.4	12.7 *	
70	90	75.9	327.9	21.0 *	76.1	323.3	19.0 *	76.1	312.9	13.5 *	76.2	306.6	10.8 *	
70	100	74.1	325.1	20.5 *	74.3	320.1	17.4 *	74.3	308.9	12.2 *	74.4	300.2	8.9 *	
70	110	72.3	321.9	19.2 *	72.4	316.5	15.8 *	72.4	308.9	11.1 *	72.5	291.4	6.6 *	
70	120	70.5	318.3	17.9 *	70.6	312.5	14.4 *							
70	130	68.6	314.3	16.8 *										

28 of 33

28p1131

HC-268

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	5 Degrees			10 Degrees			15 Degrees		
			Boom Angle (deg)	Jib Ht Height (ft)	AB-A Capacity (1000 lbs)	Boom Angle (deg)	Jib Ht Height (ft)	AB-A Capacity (1000 lbs)	Boom Angle (deg)	Jib Ht Height (ft)	AB-A Capacity (1000 lbs)
250	70	70	79.1	322.5	21.5 *	81.2	320.8	20.5 *	81.3	319.1	19.5 *
250	70	80	77.3	320.2	21.2 *	78.4	318.5	19.8 *	78.5	317.1	17.5 *
250	70	90	75.5	317.6	21.0 *	77.5	315.9	19.6 *	77.6	314.4	15.9 *
250	100	100	73.6	314.6	20.7 *	75.7	312.9	19.2 *	75.8	311.0	14.2 *
250	70	110	71.7	311.3	19.5 *	73.8	309.5	18.4 *	73.9	307.0	12.8 *
250	70	120	69.8	307.8	18.2 *	71.9	305.8	16.7 *	72.0	302.2	11.5 *
250	70	130	67.9	303.5	17.1 *	69.9	301.7	15.2 *	70.0	298.1	10.5 *
250	70	140	66.0	299.0	16.0 *	68.0	297.2	13.9 *	68.1	293.5	9.5 *
250	70	150	64.0	294.1	15.0 *	66.0	292.2	12.8 *	66.1	288.5	8.5 *
250	70	160	62.0	288.8	14.1 *	63.9	286.8	11.6 *	64.0	283.1	7.5 *
250	70	170	59.9	282.9	13.1 *	61.9	281.0	10.7 *	62.0	277.1	6.5 *
250	70	180	57.8	276.6	12.3 *	59.8	274.6	9.8 *	60.0	270.7	5.5 *
250	70	190	55.6	269.8	11.3 *	57.6	267.8	8.9 *	57.8	263.7	4.5 *
250	70	200	53.4	262.4	10.4 *	55.4	260.3	8.3 *	55.6	258.1	3.5 *
250	70	210	51.1	254.4	9.5 *	53.1	252.2	7.7 *	53.3	254.7	2.5 *
250	70	220	48.8	245.6	8.4 *	50.7	243.4	7.1 *	50.9	238.9	1.5 *
250	70	230	46.3	236.1	7.4 *	48.2	233.8	6.7 *	48.4	229.1	0.5 *
250	70	240	43.8	225.8	6.5 *	45.6	223.3	6.2 *	45.8	218.4	0.0 *
250	70	250	41.1	214.4	5.7 *	42.9	211.8	5.8 *	43.1	207.7	0.0 *
250	70	260	38.2	201.9	4.9 *	40.0	199.1	5.2 *	40.2	197.0	0.0 *
250	70	270	35.2	187.9	4.2 *	36.9	184.9	4.5 *	37.1	182.3	0.0 *
250	70	280	31.9	172.2	3.6 *						
250	70	290	28.2	154.1	3.0 *						
250	90	60	81.8	344.7	13.9 *						
250	90	70	80.0	342.9	13.7 *	80.9	338.6	12.2 *	81.5	332.0	10.4 *
250	90	80	78.3	340.7	13.4 *	79.1	336.2	11.9 *	79.8	329.2	10.3 *
250	90	90	76.6	338.3	13.1 *	77.4	333.4	11.5 *	78.0	326.0	10.0 *
250	90	100	74.9	335.5	12.9 *	75.6	330.2	11.2 *	76.2	322.5	8.9 *
250	90	110	73.1	332.4	12.6 *	73.8	326.7	10.8 *	74.3	318.6	8.0 *
250	90	120	71.3	328.9	12.3 *	72.0	322.9	10.5 *	72.5	314.3	7.2 *
250	90	130	69.6	325.1	12.0 *	70.2	318.7	9.9 *	70.6	309.7	6.5 *
250	90	140	67.7	320.9	11.6 *	68.4	314.1	9.1 *	68.7	304.6	5.8 *
250	90	150	65.9	316.3	11.2 *	66.5	309.1	8.4 *	66.7	299.1	5.2 *
250	90	160	64.0	311.4	10.6 *	64.6	303.7	7.7 *	64.8	293.2	4.8 *
250	90	170	62.1	306.0	9.8 *	62.6	297.9	7.1 *	62.7	286.7	4.3 *
250	90	180	60.2	300.2	9.1 *	60.6	291.5	6.5 *	60.7	279.8	3.9 *
250	90	190	58.2	293.9	8.4 *	58.6	284.7	6.0 *	58.5	272.3	3.6 *
250	90	200	56.2	287.2	7.8 *	56.5	277.3	5.5 *	56.3	264.1	3.3 *
250	90	210	54.1	279.9	7.3 *	54.3	269.4	5.0 *	54.1	255.4	3.1 *
250	90	220	52.0	272.0	6.7 *	52.1	260.8	4.7 *	51.7	245.8	2.8 *
250	90	230	49.8	263.5	6.2 *	49.8	251.4	4.4 *	49.2	235.5	2.6 *
250	90	240	47.5	254.2	5.8 *	47.4	241.3	4.1 *	46.7	224.2	2.4 *
250	90	250	45.1	244.3	5.4 *	44.9	230.3	3.8 *			
250	90	260	42.7	233.4	5.1 *	42.3	218.2	3.5 *			
250	90	270	40.1	221.5	4.6 *	39.5	204.9	3.3 *			
250	90	280	37.3	208.4	3.9 *	36.4	190.1	3.1 *			
250	90	290	34.4	193.8	3.3 *						
250	90	300	31.1	177.5	2.8 *						
250	90	310	27.6	158.7	2.3 *						
250	90										
260	30	50	81.3	295.8	40.0 *	80.3	293.2	40.0 *	81.2	291.5	40.0 *
260	30	60	79.3	294.0	40.0 *						

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	8 Degrees			15 Degrees			25 Degrees		
			Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)
240	80	270	37.9	205.1	5.1	40.1	201.8	3.7 *			
240	80	280	38.9	180.9	4.4	37.1	187.2	3.4 *			
240	80	300	31.6	174.8	3.8						
240	80		28.0	156.4	3.2						
250	30	80	81.0	285.7	40.0 *	79.9	283.0	40.0 *	80.9	281.4	40.0 *
250	30	70	78.9	283.8	40.0 *	77.8	280.7	40.0 *	78.8	279.1	40.0 *
250	30	60	76.8	281.8	40.0 *	75.7	278.1	40.0 *	76.7	276.4	40.0 *
250	30	50	74.7	279.0	40.0 *	73.6	275.1	40.0 *	74.5	273.4	39.0 *
250	30	40	72.6	275.9	40.0 *	71.5	271.6	38.6 *	72.4	269.9	33.5 *
250	30	30	70.5	272.5	36.3	69.3	267.7	33.4 *	70.2	266.0	30.6 *
250	30	20	68.3	268.6	31.6	67.1	263.4	30.9 *	67.9	261.6	28.0 *
250	30	10	66.1	264.3	27.3	64.8	258.6	27.9	65.7	256.8	25.6 *
250	30	0	63.8	259.5	23.8	62.5	253.3	24.3	63.3	251.5	23.5 *
250	30	180	59.2	254.2	20.8	60.1	247.5	21.3	61.0	245.6	21.6
250	30	170	56.8	248.4	18.1	57.7	241.1	18.7	58.5	239.1	19.0
250	30	160	54.3	242.0	16.3	55.2	234.0	16.4	56.0	232.0	16.7
250	30	150	51.7	235.0	14.2	52.7	226.3	14.5	53.4	224.2	14.7
250	30	140	49.1	227.4	12.5	50.0	217.9	12.8	50.7	215.7	13.0
250	30	130	46.3	218.9	11.0	47.2	208.5	11.3	47.9	206.3	11.4
250	30	120	43.4	209.7	9.7	44.3	198.2	9.9			
250	30	110	40.4	199.4	8.5	41.2	186.8	8.7			
250	30	100	37.1	188.1	7.4	37.9	174.0	6.5			
250	30	90	33.5	175.4	6.4						
250	30	80	29.6	161.0	5.5						
250	30	70	25.1	144.3	4.7						
250	30	60		124.5	3.9						
250	50	80	81.9	305.9	32.0 *	81.6	302.9	31.8 *			
250	50	70	80.0	304.2	32.0 *	79.6	300.8	31.4 *			
250	50	60	78.1	302.1	32.0 *	77.7	298.3	29.6 *	81.1	298.2	29.4 *
250	50	50	76.1	299.6	31.0 *	75.7	295.5	27.8 *	79.1	295.7	27.4 *
250	50	40	74.1	296.8	29.1 *	73.7	292.3	26.2 *	77.1	292.9	24.8 *
250	50	30	72.1	293.6	27.3 *	71.7	288.7	24.2 *	75.1	289.6	22.7 *
250	50	20	70.1	290.0	25.7 *	69.6	284.7	22.4 *	73.1	286.0	20.5 *
250	50	10	68.1	286.1	24.1 *	67.5	280.3	20.4 *	71.0	282.0	18.3 *
250	50	0	66.0	281.7	22.7 *	65.4	275.4	18.6 *	68.9	277.5	16.8 *
250	50	180	63.9	276.8	21.2 *	63.3	270.0	17.0 *	66.8	272.6	15.1 *
250	50	170	61.8	271.5	19.0	61.1	264.2	15.9 *	64.6	267.2	13.9 *
250	50	160	59.6	265.7	16.7	58.8	257.8	14.6 *	62.4	261.2	12.6 *
250	50	150	57.3	259.3	14.8	56.5	250.9	13.4 *	60.1	254.8	11.4 *
250	50	140	55.0	252.4	13.1	54.1	243.3	12.0	57.7	247.8	10.5 *
250	50	130	52.6	244.9	11.6	51.6	235.0	10.6	55.3	240.1	9.7 *
250	50	120	50.2	236.7	10.3	49.1	226.0	9.4	52.8	231.7	9.0 *
250	50	110	47.6	227.7	9.1	46.4	216.0	8.3	50.2	222.5	8.2 *
250	50	100	45.0	217.9	8.0	43.6	205.1	7.2	47.5	212.4	7.7 *
250	50	90	42.2	207.1	7.0	40.6	193.1	6.3			
250	50	80	39.2	195.1	6.1	37.4	179.5	5.4			
250	50	70	36.1	181.7	5.2						
250	50	60	32.6	166.7	4.5						
250	50	50	28.8	149.3	3.8						
250	50	40		324.4	21.8 *						

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	5 Degrees				15 Degrees				25 Degrees			
			Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)
240	50	200	48.5	223.3	10.7	50.0	221.6	11.0	51.2	218.2	9.4	52.4	214.8	8.7
240	50	210	45.8	213.8	9.5	47.3	212.0	9.7	48.4	208.4	8.7	49.5	204.8	8.0
240	50	220	43.0	203.2	8.4	44.4	201.4	8.6	45.5	197.8	7.9	46.6	194.2	7.2
240	50	230	39.9	191.6	7.4	41.3	189.6	7.6	42.4	186.0	6.9	43.5	182.4	6.2
240	50	240	36.7	178.5	6.5	38.1	176.4	6.7	39.2	172.8	6.0	40.3	169.2	5.3
240	50	250	33.2	163.8	5.7									
240	50	260	29.4	146.8	4.9									
240	70	60	80.6	314.3	21.7 *	80.9	310.6	20.2 *	81.0	304.8	18.3 *	81.1	301.1	16.8 *
240	70	70	78.8	312.3	21.5 *	79.0	308.2	19.9 *	79.1	302.1	17.0 *	79.2	298.4	15.5 *
240	70	80	76.9	309.9	21.2 *	77.1	305.5	19.5 *	77.2	298.9	16.6 *	77.3	295.2	15.1 *
240	70	90	75.0	307.2	20.9 *	75.2	302.4	19.1 *	75.2	295.4	14.9 *	75.2	291.5	13.4 *
240	70	100	73.1	304.1	20.6 *	73.2	298.9	18.7 *	73.2	291.5	13.4 *	73.2	287.2	12.0 *
240	70	110	71.1	300.7	19.7 *	71.2	295.0	17.6 *	71.1	287.2	10.9 *	71.1	282.4	9.8 *
240	70	120	69.1	296.8	18.4 *	69.2	290.8	16.0 *	69.1	282.4	8.9 *	69.1	277.2	8.2 *
240	70	130	67.2	292.6	17.3 *	67.2	286.1	14.7 *	67.0	277.2	8.2 *	67.0	271.5	7.4 *
240	70	140	65.1	287.9	16.2 *	65.1	280.9	12.1 *	64.8	271.5	6.7 *	64.8	265.3	6.1 *
240	70	150	63.1	282.8	15.2 *	63.0	275.3	11.3 *	62.6	265.3	5.8 *	62.6	258.6	5.1 *
240	70	160	61.0	277.3	14.3 *	60.9	269.2	10.3 *	60.4	258.6	4.8 *	60.4	251.3	4.1 *
240	70	170	58.8	271.2	13.5 *	58.6	262.6	9.4 *	58.1	243.3	3.9 *	58.1	234.5	3.2 *
240	70	180	56.6	264.6	12.7 *	56.4	255.4	8.8 *	56.2	234.5	2.9 *	56.2	225.0	2.3 *
240	70	190	54.4	257.4	11.9 *	54.0	247.5	8.1 *	53.2	225.0	2.3 *	53.2	214.6	1.7 *
240	70	200	52.0	249.6	11.0 *	51.6	239.0	7.4 *	50.6	214.6	1.7 *	50.6	203.1	1.1 *
240	70	210	49.6	241.2	10.0 *	49.1	229.6	6.5 *	48.1	203.1	1.1 *	48.1	191.6	0.5 *
240	70	220	47.1	231.9	8.9 *	46.4	219.4	5.9 *	45.1	191.6	0.5 *	45.1	179.1	0.0 *
240	70	230	44.5	221.8	7.9 *	43.7	208.2	5.2 *						
240	70	240	41.8	210.7	7.0 *	40.7	195.8	4.5 *						
240	70	250	38.9	198.5	6.2 *	37.6	181.9	3.8 *						
240	70	260	35.8	184.8	5.4 *									
240	70	270	32.4	169.4	4.7 *									
240	70	280	28.7	151.6	4.0 *									
240	90	60	81.5	334.6	13.9 *	80.6	328.4	12.2 *	81.3	321.7	10.4 *	81.4	318.0	9.0 *
240	90	70	79.7	332.7	13.6 *	78.8	325.8	11.8 *	79.4	318.8	10.3 *	79.5	315.1	8.9 *
240	90	80	78.0	330.5	13.3 *	77.0	322.9	11.4 *	77.6	315.5	9.3 *	77.7	311.9	8.3 *
240	90	90	76.2	327.9	13.1 *	75.2	319.7	11.1 *	75.7	311.9	8.3 *	75.8	307.8	7.4 *
240	90	100	74.4	325.0	12.8 *	73.3	316.1	10.7 *	73.8	307.8	6.6 *	73.9	303.4	5.8 *
240	90	110	72.6	321.8	12.5 *	71.5	312.1	10.3 *	71.9	298.6	5.0 *	72.0	294.2	4.2 *
240	90	120	70.8	318.2	11.8 *	69.6	307.8	9.6 *	69.9	293.3	3.9 *	70.0	288.9	3.1 *
240	90	130	68.9	314.3	11.5 *	67.6	303.0	8.7 *	68.0	287.6	2.7 *	68.1	283.2	2.0 *
240	90	140	67.0	310.0	11.1 *	65.7	297.8	8.0 *	65.9	281.4	2.0 *	66.0	277.0	1.3 *
240	90	150	65.1	305.2	10.7 *	63.7	292.2	7.2 *	63.9	274.7	1.3 *	64.0	269.3	0.6 *
240	90	160	63.2	300.1	10.2 *	61.7	286.1	6.7 *	61.8	267.4	0.6 *	61.9	262.9	0.0 *
240	90	170	61.2	294.5	9.5 *	59.6	279.5	6.2 *	59.6	259.5	0.0 *	59.7	255.0	-0.6 *
240	90	180	59.2	288.5	8.8 *	57.5	272.4	5.7 *	57.3	251.0	-0.6 *	57.4	246.5	-1.2 *
240	90	190	57.1	281.9	8.1 *	55.3	264.7	5.2 *	55.0	241.7	-1.2 *	55.1	237.2	-1.8 *
240	90	200	55.0	274.9	7.6 *	53.0	256.3	4.9 *	52.6	231.6	-1.8 *	52.7	227.1	-2.4 *
240	90	210	52.8	267.2	7.1 *	50.7	247.2	4.5 *	50.1	220.6	-2.4 *	50.2	216.1	-3.0 *
240	90	220	50.6	258.9	6.6 *	48.2	237.3	4.2 *	47.5	211.1	-3.0 *	47.6	206.6	-3.6 *
240	90	230	48.3	249.9	6.1 *	45.7	226.6	3.9 *						
240	90	240	45.9	240.2	5.7 *	43.0	214.8	3.6 *						
240	90	250	43.4	229.6	5.4 *									
240	90	260	40.7	217.9	5.1 *									

28p1131

1/2

Select

Convent Boom

Load H

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	8 Degrees			15 Degrees			28 Degrees		
			Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)
230	90	150	64.3	284.1	10.9	66.9	291.8	9.9	69.2	287.4	6.9
230	90	160	62.3	288.7	10.5	64.8	286.5	9.0	67.2	281.9	6.3
230	90	170	60.2	282.9	10.3	62.8	280.6	8.3	65.1	276.0	5.8
230	90	180	58.1	276.8	9.8	60.6	274.2	7.7	62.9	269.5	5.1
230	90	190	56.0	270.8	9.1	58.5	267.3	7.1	60.7	262.5	4.7
230	90	200	53.7	264.3	8.6	56.2	259.8	6.6	58.4	254.9	4.3
230	90	210	51.5	257.7	7.4	53.9	251.7	6.0	56.1	246.6	3.9
230	90	220	49.1	250.1	6.9	51.5	242.9	5.6	53.6	237.5	3.6
230	90	230	46.6	241.3	6.1	49.1	233.3	5.1	51.1	227.7	3.3
230	90	240	44.1	231.8	5.7	46.5	222.8	4.7	48.4	216.9	3.0
230	90	250	41.4	221.3	5.4	43.7	211.3	4.4	45.6	205.0	2.9
230	90	260	38.5	209.8	5.0	40.8	198.5	4.1			
230	90	270	35.5	197.1	4.6	37.7	184.3	3.9			
230	90	280	32.2	183.0	4.2						
240	30	50	80.6	275.5	40.0	81.7	274.7	40.0	80.5	271.1	40.0
240	30	60	78.5	273.6	40.0	79.6	272.8	40.0	78.4	268.8	40.0
240	30	70	76.3	271.3	40.0	77.4	270.4	40.0	76.2	266.0	40.0
240	30	80	74.2	268.5	40.0	75.2	267.7	40.0	73.9	262.8	40.0
240	30	90	72.0	265.4	40.0	73.0	264.5	40.0	71.7	259.2	38.1
240	30	100	69.7	261.8	36.6	70.7	260.9	40.0	69.4	255.2	32.9
240	30	110	67.5	257.8	32.0	68.5	256.9	37.2	67.0	250.6	29.8
240	30	120	65.1	253.3	27.7	66.2	252.4	32.5	64.7	245.5	27.3
240	30	130	62.8	248.3	24.2	63.8	247.4	28.2	62.2	239.9	25.0
240	30	140	60.4	242.7	21.3	61.4	241.8	24.6	59.7	233.8	21.9
240	30	150	57.9	236.6	18.7	58.9	235.7	21.6	57.2	227.0	19.3
240	30	160	55.4	229.9	16.5	56.4	228.9	19.0	54.5	219.5	17.1
240	30	170	52.8	222.5	14.6	53.7	221.5	16.8	51.8	211.2	15.1
240	30	180	50.1	214.4	13.0	51.0	213.3	14.8	48.9	202.1	13.3
240	30	190	47.2	205.4	11.5	48.2	204.3	13.1	45.9	192.0	11.8
240	30	200	44.3	195.5	10.1	45.2	194.3	11.6			10.4
240	30	210	41.1	184.4	8.9	42.0	183.2	10.2			
240	30	220	37.8	172.0	7.9	38.6	170.7	9.0			
240	30	230	34.1	158.0	6.9			7.9			
240	30	240	30.1	141.7	6.0						
240	30	250	25.5	122.3	5.2						
240	50	50	81.6	295.8	32.0	81.3	292.7	31.8	80.8	288.0	29.3
240	50	60	79.6	294.0	32.0	79.3	290.5	31.3	78.8	285.4	28.2
240	50	70	77.6	291.8	32.0	77.2	288.0	30.1	76.7	282.4	26.4
240	50	80	75.6	289.3	31.6	75.2	285.0	28.3	74.6	279.1	23.8
240	50	90	73.6	286.4	29.6	73.1	281.7	26.6	72.5	275.3	21.5
240	50	100	71.5	283.0	27.8	71.0	278.0	25.1	70.3	271.1	19.4
240	50	110	69.4	279.3	26.1	68.9	273.8	23.6	68.1	266.4	17.6
240	50	120	67.3	275.2	24.5	66.7	269.2	21.7	65.9	261.3	16.0
240	50	130	65.1	270.6	23.0	64.5	264.1	20.0	63.6	255.6	14.5
240	50	140	62.9	265.5	21.7	62.2	258.5	18.3	61.3	249.4	13.3
240	50	150	60.7	260.0	19.4	59.9	252.4	16.8	58.9	242.7	12.2
240	50	160	58.4	253.9	17.2	57.6	245.7	15.4	56.4	235.3	11.0
240	50	170	56.0	247.3	15.2	55.1	238.4	13.9	53.8	227.1	10.2
240	50	180	53.6	240.0	13.6	52.6	230.4	12.4			
240	50	190	51.1	232.0	12.0						

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	8 Degrees			18 Degrees			25 Degrees		
			Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)
220	70	230	80.3	181.5	8.6	45.3	185.9	7.9 *			
220	70	240	37.1	178.5	7.7	39.0	175.7	7.4 *			
220	70	250	33.8	163.7	6.9	35.4	160.7	6.8 *			
220	70	260	29.7	146.7	6.2						
220	70	270	25.3	126.4	5.5						
220	80	60	81.0	314.2	13.8 *	81.9	310.2	12.4 *	80.7	301.1	10.4 *
220	80	70	79.1	312.2	13.5 *	80.0	307.9	12.0 *	78.7	297.9	10.2 *
220	80	80	77.2	309.6	13.2 *	78.1	305.1	11.7 *	76.7	294.4	10.1 *
220	80	90	75.3	307.1	12.9 *	76.1	302.0	11.3 *	74.7	290.5	9.7 *
220	80	100	73.4	304.1	12.7 *	74.2	298.5	10.9 *	72.7	286.2	9.4 *
220	80	110	71.4	300.6	12.3 *	72.2	294.7	10.5 *	70.6	281.4	8.7 *
220	80	120	69.5	296.8	11.9 *	70.2	290.4	10.3 *	68.5	276.2	7.9 *
220	80	130	67.5	292.5	11.5 *	68.1	285.7	10.0 *	66.3	270.5	7.2 *
220	80	140	65.4	287.9	11.1 *	66.1	280.6	9.5 *	64.1	264.2	6.4 *
220	80	150	63.4	282.8	10.7 *	63.9	275.0	9.0 *	61.9	257.5	5.9 *
220	80	160	61.3	277.2	10.3 *	61.8	268.8	8.6 *	59.6	250.1	5.4 *
220	80	170	59.1	271.1	10.0 *	59.6	262.2	8.0 *	57.2	242.0	4.9 *
220	80	180	56.9	264.6	9.9 *	57.3	254.9	7.3 *	54.7	233.3	4.4 *
220	80	190	54.7	257.4	9.3 *	54.9	247.1	6.7 *	52.1	223.7	3.7 *
220	80	200	52.4	249.6	8.8 *	52.5	238.5	6.3 *	49.4	213.2	3.5 *
220	80	210	49.9	241.1	8.3 *	50.0	229.2	5.8 *	46.5	201.6	3.3 *
220	80	220	47.4	231.9	7.9 *	47.3	218.9	5.3 *			
220	80	230	44.8	221.8	7.4 *	44.5	207.7	4.7 *			
220	80	240	42.1	210.7	6.9 *	41.6	195.2	4.4 *			
220	80	250	39.2	198.4	6.4 *	38.4	181.3				
220	80	260	36.1	184.7	6.1 *						
220	80	270	32.7	169.3	5.7 *						
220	80	280	29.0	151.6	5.2						
230	30	50	80.3	265.4	40.0 *	81.4	264.6	40.0 *	80.2	260.9	40.0 *
230	30	60	78.1	263.4	40.0 *	79.1	262.6	40.0 *	77.9	258.5	40.0 *
230	30	70	75.8	261.0	40.0 *	76.9	260.1	40.0 *	75.6	255.6	40.0 *
230	30	80	73.5	258.1	40.0 *	74.6	257.3	40.0 *	73.3	252.3	40.0 *
230	30	90	71.2	254.8	40.0 *	72.3	254.0	40.0 *	70.9	248.5	40.0 *
230	30	100	68.9	251.1	40.0 *	70.0	250.2	40.0 *	68.5	244.2	35.6 *
230	30	110	66.5	246.9	37.0	67.6	246.0	37.6	66.1	239.5	32.2 *
230	30	120	64.1	242.2	32.3	65.2	241.3	32.8	63.6	234.2	28.9
230	30	130	61.7	236.9	28.1	62.7	236.0	28.5	61.0	228.3	25.3
230	30	140	59.1	231.1	24.6	60.2	230.1	25.0	58.4	221.8	22.3
230	30	150	56.5	224.7	21.6	57.5	223.7	21.9	55.7	214.6	19.6
230	30	160	53.9	217.6	19.1	54.9	216.6	19.4	52.9	206.6	17.4
230	30	170	51.1	209.7	16.9	52.1	208.7	17.1	49.9	197.8	15.4
230	30	180	48.2	201.0	15.0	49.2	200.0	15.2	46.8	188.0	13.7
230	30	190	45.2	191.4	13.3	46.1	190.3	13.5			12.1
230	30	200	41.9	180.7	11.8	42.9	179.5	12.0			
230	30	210	38.5	168.6	10.5	39.4	167.3	10.6			
230	30	220	34.8	154.9	9.3	35.7	153.5	9.4			
230	30	230	30.7	139.0	8.2			8.3			
230	30	240	26.0	120.1	7.2						
50	50	81.3	285.6	32.0 *							
50	50	79.3	283.8	32.0 *							
81.0				282.5	31.7 *						

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	5 Degrees			15 Degrees			25 Degrees			35 Degrees		
			Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)
220	30	120	63.0	230.8	28.4	64.1	230.0	28.8	65.0	228.3	29.2	65.0	228.3	29.2
220	30	130	60.4	225.4	24.9	61.5	224.5	25.3	62.4	222.6	25.6	62.4	222.6	25.6
220	30	140	57.8	219.3	22.0	58.8	218.3	22.3	59.7	216.4	22.6	59.7	216.4	22.6
220	30	150	55.0	212.5	19.5	56.1	211.5	19.7	56.9	209.4	20.0	56.9	209.4	20.0
220	30	160	52.2	204.9	17.3	53.2	203.9	17.5	54.0	201.9	17.7	54.0	201.9	17.7
220	30	170	49.2	196.6	15.4	50.2	195.5	15.5	51.0	193.4	15.7	51.0	193.4	15.7
220	30	180	46.1	187.3	13.7	47.1	186.1	13.8	47.9	183.9	14.0	47.9	183.9	14.0
220	30	190	42.8	176.9	12.2	43.8	175.7	12.3						
220	30	200	39.3	165.2	10.9	40.3	163.9	11.0						
220	30	210	35.5	151.8	9.7	36.4	150.4	9.7						
220	30	220	31.3	136.3	8.6									
220	30	230	26.6	117.8	7.6									
220	50	50	81.0	275.5	32.0 *	80.6	272.3	31.6 *	80.1	267.4	29.2 *	77.9	264.6	27.6 *
220	50	60	78.9	273.6	32.0 *	78.5	269.9	31.1 *	77.9	264.6	27.6 *	75.6	261.4	26.0 *
220	50	70	76.7	271.2	32.0 *	76.3	267.2	30.5 *	75.6	261.4	24.6 *	73.4	257.8	23.4 *
220	50	80	74.5	268.5	32.0 *	74.1	264.0	29.1 *	73.4	257.8	21.7 *	71.1	253.7	20.0 *
220	50	90	72.3	265.3	30.5 *	71.8	260.4	27.4 *	71.1	253.7	18.0 *	68.7	249.1	16.3 *
220	50	100	70.1	261.8	28.6 *	69.5	256.4	25.8 *	68.7	249.1	15.1 *	66.3	244.0	13.7 *
220	50	110	67.8	257.7	26.8 *	67.2	251.8	24.3 *	66.3	244.0	12.5 *	63.9	238.4	11.6 *
220	50	120	65.5	253.2	25.2 *	64.8	246.8	22.9 *	63.9	238.4	10.8 *	61.4	232.2	10.8 *
220	50	130	63.2	248.2	23.7 *	62.4	241.2	21.7 *	61.4	225.3	9.2 *	58.8	217.8	8.2 *
220	50	140	60.7	242.7	22.3 *	59.9	235.1	20.5 *	58.8	217.8	7.5 *	56.1	209.4	6.8 *
220	50	150	58.3	236.6	20.1	57.4	228.3	18.3	56.1	209.4	6.0 *	53.3	200.2	5.8 *
220	50	160	55.7	229.8	17.9	54.7	220.9	16.3	50.4	190.0		47.4		
220	50	170	53.1	222.5	16.0	52.0	212.7	14.6						
220	50	180	50.4	214.3	14.3	49.2	203.6	13.1						
220	50	190	47.6	205.3	12.8	46.2	193.6	11.7						
220	50	200	44.6	195.4	11.5	43.0	182.4	10.4						
220	50	210	41.5	184.3	10.3	39.6	169.9	9.3						
220	50	220	38.1	171.9	9.2	35.9	155.6	8.3						
220	50	230	34.5	157.9	8.2									
220	50	240	30.5	141.6	7.3									
220	50	250	25.9	122.2	6.5									
220	70	50	82.0	295.7	21.9 *	80.3	290.1	20.1 *	80.4	284.2	18.2 *	78.3	281.2	17.6 *
220	70	60	80.0	293.9	21.3 *	78.2	287.5	19.7 *	76.2	277.9	16.7 *	74.1	274.1	15.9 *
220	70	70	78.0	291.8	21.0 *	76.2	284.6	18.9 *	74.1	269.9	14.5 *	71.9	265.2	13.1 *
220	70	80	76.0	289.2	20.7 *	74.1	281.3	18.5 *	71.9	260.0	11.8 *	69.7	254.3	10.7 *
220	70	90	73.9	286.3	20.4 *	72.0	277.5	18.1 *	69.7	250.0	9.8 *	67.5	248.1	8.9 *
220	70	100	71.8	283.0	20.0 *	69.9	273.4	17.0 *	67.5	244.0	8.1 *	65.2	233.8	7.5 *
220	70	110	69.8	279.3	18.8 *	67.7	268.7	16.0 *	65.2	238.4	6.8 *	62.8	225.7	6.2 *
220	70	120	67.6	275.1	17.6 *	65.5	263.7	14.8 *	62.8	225.7	5.8 *	60.4	216.7	5.8 *
220	70	130	65.5	270.5	16.5 *	63.2	258.1	13.6 *	60.4	209.4		57.9	195.9	
220	70	140	63.3	265.5	15.5 *	60.9	251.9	12.6 *	55.4	183.9		52.7		
220	70	150	61.0	259.9	14.6 *	58.5	245.2	11.6 *	49.9			46.9		
220	70	160	58.7	253.9	13.7 *	56.1	237.9	10.6 *						
220	70	170	56.4	247.2	12.9 *	53.6	229.9	9.9 *						
220	70	180	54.0	239.9	12.2 *	50.9	221.1	9.2 *						
220	70	190	51.5	232.0	11.6 *	48.2	211.4	8.5 *						
220	70	200	48.9	223.3	10.7	45.3	200.8							
220	70	210	46.1	213.7	9.6									
220	70	220	43.3	203.2										

28p1131

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	5 Degrees			15 Degrees			25 Degrees		
			Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)
210	70	60	79.6	283.7	21.6 *	79.9	279.8	20.0 *	80.0	273.9	18.1 *
210	70	70	77.5	281.5	21.3 *	77.8	277.2	19.6 *	77.9	270.8	17.5 *
210	70	80	75.4	278.8	21.0 *	75.7	274.1	19.2 *	75.7	267.3	16.5 *
210	70	90	73.3	275.8	20.6 *	73.5	270.7	18.8 *	73.5	263.3	15.6 *
210	70	100	71.2	272.4	20.3 *	71.3	266.8	18.3 *	71.2	258.9	14.9 *
210	70	110	69.0	268.5	19.8 *	69.1	262.4	18.0 *	68.9	254.0	13.7 *
210	70	120	66.8	264.2	19.0 *	66.8	257.6	17.2 *	66.6	248.6	12.4 *
210	70	130	64.5	259.4	17.8 *	64.5	252.3	16.2 *	64.2	242.7	11.2 *
210	70	140	62.2	254.1	16.6 *	62.2	246.4	15.2 *	61.7	236.2	10.1 *
210	70	150	59.9	248.3	15.6 *	59.7	240.0	14.4 *	59.2	229.0	9.2 *
210	70	160	57.5	241.9	14.7 *	57.2	232.9	13.1 *	56.5	221.1	8.5 *
210	70	170	55.0	234.9	13.8 *	54.6	225.2	12.3 *	53.8	212.4	7.8 *
210	70	180	52.4	227.2	13.1 *	52.0	216.7	11.3 *	50.9	202.8	7.1 *
210	70	190	49.8	218.8	12.3 *	49.2	207.3	10.4 *	47.9	192.2	6.6 *
210	70	200	47.0	209.5	11.7 *	46.2	196.9	9.7 *			
210	70	210	44.1	199.3	11.1 *	43.1	185.4	8.9 *			
210	70	220	41.0	187.9	10.0	39.8	172.5	8.3 *			
210	70	230	37.7	175.2	9.0	36.1	157.8	7.9 *			
210	70	240	34.2	160.8	8.1						
210	70	250	30.2	144.1	7.3						
210	70	260	25.7	124.3	6.5						
210	90	60	80.6	304.1	13.7 *	81.6	300.0	12.4 *	80.3	290.7	10.3 *
210	90	70	78.7	302.0	13.5 *	79.6	297.6	12.0 *	78.3	287.5	10.2 *
210	90	80	76.8	299.5	13.2 *	77.6	294.7	11.6 *	76.2	283.8	10.1 *
210	90	90	74.8	296.7	12.9 *	75.6	291.5	11.2 *	74.2	279.7	9.9 *
210	90	100	72.8	293.5	12.6 *	73.6	287.9	10.8 *	72.0	275.2	9.1 *
210	90	110	70.8	290.0	12.2 *	71.6	283.9	10.4 *	69.9	270.3	8.2 *
210	90	120	68.7	286.0	11.8 *	69.5	279.4	10.3 *	67.7	264.8	7.3 *
210	90	130	66.7	281.6	11.4 *	67.3	274.6	10.1 *	65.4	258.8	6.7 *
210	90	140	64.6	276.7	11.0 *	65.2	269.2	10.0 *	63.1	252.3	6.1 *
210	90	150	62.4	271.4	10.5 *	63.0	263.3	9.6 *	60.8	245.2	5.5 *
210	90	160	60.2	265.6	10.3 *	60.7	256.9	8.9 *	58.3	237.4	5.1 *
210	90	170	58.0	259.2	10.2 *	58.4	250.0	8.3 *	55.8	228.9	4.7 *
210	90	180	55.7	252.3	9.9 *	56.0	242.3	7.7 *	53.1	219.6	4.3 *
210	90	190	53.3	244.8	9.4 *	53.5	234.0	7.0 *	50.4	209.4	3.9 *
210	90	200	50.8	236.6	8.8 *	50.9	224.9	6.5 *	47.4	198.1	3.6 *
210	90	210	48.3	227.6	8.4 *	48.2	215.0	6.1 *			
210	90	220	45.6	217.8	7.9 *	45.4	204.0	5.7 *			
210	90	230	42.8	206.9	7.5 *	42.4	191.9	5.3 *			
210	90	240	39.9	195.0	7.2 *	39.2	178.3	4.9 *			
210	90	250	36.7	181.6	6.8 *	35.6	162.8	4.6 *			
210	90	260	33.3	166.5	6.4 *						
210	90	270	29.5	149.1	6.1 *						
210	90	280	25.1	128.4	5.5						
30	50		79.9	255.2	40.0 *	81.0	254.4	40.0 *	79.8	250.7	40.0 *
30	60		77.6	253.1	40.0 *	78.7	252.3	40.0 *	77.4	248.1	40.0 *
30	70		75.2	250.6	40.0 *	76.4	249.8	40.0 *	75.0	245.1	40.0 *
30	80		72.9	247.6	40.0 *	74.0	246.8	40.0 *	72.6	241.7	39.7 *
30	90		70.5	244.2	40.0 *	71.6	243.3	40.0 *	70.1	237.7	37.7 *
100	68.0		240.3	37.4	69.1	239.4	37.9	67.6	233.2	33.6	
110	65.5		235.9	32.7	66.6	235.0	33.1				

Refer to all notes in front of the Crane Rating Manual before operating this machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	5 Degrees			14 Degrees			28 Degrees		
			Boom Angle (deg)	Jib Height (ft)	AB-A Capacity (1000 lbs)	Boom Angle (deg)	Jib Height (ft)	AB-A Capacity (1000 lbs)	Boom Angle (deg)	Jib Height (ft)	AB-A Capacity (1000 lbs)
200	90	180	54.3	238.8	9.8 *	57.1	237.5	8.5 *	58.5	232.7	8.7 *
200	90	190	51.8	231.8	9.4 *	54.5	229.5	7.9 *	56.9	224.5	8.2 *
200	90	200	49.2	223.2	8.9 *	51.8	220.7	7.3 *	54.2	216.5	7.8 *
200	90	210	46.5	213.7	8.4 *	49.2	211.0	6.8 *	51.4	207.8	7.3 *
200	90	220	43.8	203.1	8.0 *	46.3	200.3	6.4 *	48.4	194.5	6.9 *
200	90	230	40.6	191.5	7.6 *	43.2	188.4	5.9 *	45.3	182.3	6.4 *
200	90	240	37.4	178.4	7.2 *	39.9	175.2	5.5 *			
200	90	250	33.9	163.6	6.8 *	36.4	160.1	5.1 *			
200	90	260	30.0	146.6	6.4 *						
200	90	270	25.6	126.3	6.0 *						
210	30	40	81.9	246.8	40.0 *						
210	30	50	79.5	245.0	40.0 *	80.7	244.2	40.0 *	81.8	242.6	40.0 *
210	30	60	77.1	242.8	40.0 *	78.2	242.0	40.0 *	79.3	240.4	40.0 *
210	30	70	74.6	240.2	40.0 *	75.8	239.4	40.0 *	76.9	237.7	40.0 *
210	30	80	72.1	237.1	40.0 *	73.3	236.3	40.0 *	74.4	234.6	40.0 *
210	30	90	69.6	233.5	40.0 *	70.8	232.7	40.0 *	71.8	231.0	39.1 *
210	30	100	67.1	229.4	37.7	68.2	228.5	36.2	69.2	226.8	37.1 *
210	30	110	64.5	224.8	33.0	65.6	223.9	33.4	66.6	222.1	33.9
210	30	120	61.8	219.6	28.8	62.9	218.7	29.2	63.9	216.9	29.5
210	30	130	59.1	213.8	25.3	60.2	212.8	25.6	61.1	211.0	25.9
210	30	140	56.2	207.3	22.4	57.3	206.3	22.6	58.3	204.4	22.9
210	30	150	53.3	200.1	19.8	54.4	199.1	20.0	55.3	197.1	20.3
210	30	160	50.3	192.0	17.7	51.3	191.0	17.8	52.2	188.9	18.0
210	30	170	47.1	183.0	15.7	48.2	181.9	15.9	49.0	179.7	16.1
210	30	180	43.8	173.0	14.1	44.8	171.8	14.2	45.6	169.5	14.3
210	30	190	40.2	161.6	12.6	41.2	160.3	12.7			
210	30	200	36.3	148.6	11.3	37.3	147.3	11.3			
210	30	210	32.0	133.5	10.1						
210	30	220	27.1	115.5	9.0						
210	50	50	80.7	265.3	32.0 *	80.3	262.1	31.5 *	82.0	259.6	29.4 *
210	50	60	78.4	263.3	32.0 *	78.0	259.6	31.0 *	79.7	257.1	29.0 *
210	50	70	76.2	260.9	32.0 *	75.7	256.8	30.4 *	77.4	254.2	27.2 *
210	50	80	73.9	258.0	32.0 *	73.4	253.5	29.5 *	75.1	250.9	25.7 *
210	50	90	71.6	254.8	30.9 *	71.1	249.7	27.7 *	72.7	247.1	24.3 *
210	50	100	69.3	251.0	28.9 *	68.7	245.5	26.1 *	70.3	242.8	23.0 *
210	50	110	66.9	246.8	27.1 *	66.3	240.7	24.6 *	67.8	238.0	22.0 *
210	50	120	64.5	242.1	25.5 *	63.8	235.4	23.2 *	65.3	232.6	20.9 *
210	50	130	62.0	236.8	23.9 *	61.2	229.6	21.9 *	62.7	226.7	19.0 *
210	50	140	59.5	231.0	22.5 *	58.6	223.1	20.7 *	60.1	220.2	17.6 *
210	50	150	56.9	224.6	20.5	55.9	216.0	18.6	57.4	212.9	16.0 *
210	50	160	54.2	217.5	18.3	53.1	208.1	16.7	54.5	204.9	14.6 *
210	50	170	51.4	209.6	16.4	50.2	199.3	15.0	51.5	196.0	13.3 *
210	50	180	48.6	201.0	14.7	47.1	189.6	13.4	48.4	186.1	12.3 *
210	50	190	45.5	191.3	13.2	43.9	178.7	12.0	45.1	175.0	11.5 *
210	50	200	42.3	180.6	11.8	40.4	166.5	10.8			
210	50	210	38.9	168.5	10.6	36.7	152.6	9.7			
210	50	220	35.2	154.8	9.6						
210	50	230	31.1	138.9	8.6						
210	50	240	26.4	120.0	7.7						
210	70	50	81.7	285.6	21.9 *						

28p1131

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	5 Degrees				15 Degrees				25 Degrees			
			Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)
200	50	60	78.0	253.1	32.0 *	79.9	251.8	31.4 *	81.7	249.3	29.4 *	83.5	246.8	27.9 *
200	50	70	75.8	250.5	32.0 *	77.5	248.3	30.8 *	79.3	246.8	28.7 *	81.1	244.3	26.9 *
200	50	80	73.3	247.8	32.0 *	75.1	245.3	30.2 *	76.9	243.8	28.0 *	78.7	241.3	26.3 *
200	50	90	70.9	244.1	31.2 *	72.7	242.8	29.6 *	74.4	240.3	27.0 *	76.2	237.8	25.7 *
200	50	100	68.4	240.2	29.2 *	70.3	238.9	28.0 *	72.0	235.3	25.3 *	73.8	232.8	23.9 *
200	50	110	65.8	235.6	27.4 *	67.8	234.5	26.3 *	69.4	231.8	22.7 *	71.2	229.3	21.6 *
200	50	120	63.4	230.9	25.7 *	65.2	229.5	24.8 *	66.8	226.8	20.6 *	68.6	224.3	19.8 *
200	50	130	60.8	225.4	24.2 *	62.6	223.9	23.4 *	64.2	221.1	19.8 *	66.0	218.6	18.5 *
200	50	140	58.1	219.2	22.7 *	59.9	217.8	22.2 *	61.5	214.9	18.5 *	63.4	212.4	17.3 *
200	50	150	55.4	212.4	20.8 *	57.2	210.9	20.9 *	58.7	209.9	17.0 *	60.7	207.9	16.5 *
200	50	160	52.5	204.9	18.6 *	54.3	203.3	19.0 *	55.8	200.2	16.5 *	57.9	197.9	15.4 *
200	50	170	49.6	196.5	16.7 *	51.3	194.9	17.0 *	52.7	191.6	15.4 *	54.9	189.1	14.1 *
200	50	180	46.6	187.2	15.0 *	48.2	185.5	15.3 *	49.5	182.1	13.1 *	51.9	179.6	11.9 *
200	50	190	43.2	176.8	13.5 *	44.9	175.0	13.7 *	46.2	171.3	11.1 *	48.9	168.8	9.9 *
200	50	200	39.7	165.1	12.2 *	41.3	163.1	12.4 *	42.6	159.6	8.9 *	45.7	157.1	7.7 *
200	50	210	35.9	151.7	11.0 *	37.5	149.6	11.1 *	38.8	146.1	6.9 *	41.9	143.6	5.7 *
200	50	220	31.7	136.2	9.9 *	33.5	134.1	9.9 *	34.8	130.6	5.7 *	38.9	128.1	4.5 *
200	50	230	26.9	117.7	8.9 *	29.3	112.1	8.9 *	30.6	108.6	4.5 *	34.9	106.1	3.3 *
200	70	50	81.4	275.5	21.9 *	81.7	271.9	20.4 *	81.9	266.3	18.4 *	82.1	261.7	16.9 *
200	70	60	79.2	273.5	21.5 *	79.5	269.5	20.0 *	79.7	263.5	18.1 *	80.0	259.1	16.5 *
200	70	70	77.1	271.2	21.2 *	77.3	266.8	19.5 *	77.4	260.3	17.3 *	77.6	255.7	15.3 *
200	70	80	74.9	268.4	20.9 *	75.1	263.6	18.6 *	75.1	256.6	15.4 *	75.2	251.2	14.0 *
200	70	90	72.7	265.3	20.1 *	72.9	260.0	17.3 *	72.8	252.5	13.7 *	72.9	247.9	12.7 *
200	70	100	70.4	261.7	19.7 *	70.6	256.0	16.3 *	70.5	242.8	11.7 *	70.6	240.0	10.6 *
200	70	110	68.2	257.7	18.1 *	68.3	251.4	14.4 *	68.0	237.1	10.6 *	68.1	233.6	9.7 *
200	70	120	65.9	253.2	16.8 *	65.9	246.4	13.7 *	65.6	230.9	9.7 *	65.7	227.4	8.8 *
200	70	130	63.5	248.2	15.7 *	63.5	240.8	12.8 *	63.1	224.0	8.8 *	63.2	220.9	7.5 *
200	70	140	61.1	242.6	14.8 *	61.0	234.6	11.8 *	60.5	216.4	7.5 *	60.6	213.3	6.9 *
200	70	150	58.6	236.5	13.9 *	58.4	227.9	10.2 *	57.8	208.0	6.9 *	57.9	205.0	5.7 *
200	70	160	56.1	229.8	12.4 *	55.8	220.4	9.6 *	55.0	198.7	5.7 *	55.1	195.7	4.5 *
200	70	170	53.5	222.4	11.2 *	53.0	212.2	8.9 *	52.0	188.4	4.5 *	52.1	185.4	3.3 *
200	70	180	50.8	214.3	10.4 *	50.2	203.1	8.0 *	49.0	180.9	3.3 *	49.1	177.9	2.1 *
200	70	190	47.9	205.3	9.4 *	47.2	193.0	7.1 *	46.0	176.9	2.1 *	46.1	173.9	0.9 *
200	70	200	45.0	195.3	8.5 *	44.0	181.8	6.2 *	43.0	170.9	0.9 *	43.1	167.9	-0.1 *
200	70	210	41.8	184.3	7.7 *	40.6	169.2	5.3 *	39.0	164.4	-0.1 *	39.1	161.4	-1.3 *
200	70	220	38.5	171.9	6.9 *	36.9	154.9	4.5 *	35.0	159.4	-1.3 *	35.1	156.4	-2.5 *
200	70	230	34.8	157.8	6.1 *	33.1	140.9	3.7 *	31.0	144.9	-2.5 *	31.1	141.9	-3.7 *
200	70	240	30.8	141.5	5.3 *	29.3	126.4	2.9 *	27.0	130.9	-3.7 *	27.1	127.9	-4.9 *
200	70	250	26.2	122.1	4.5 *	25.5	111.9	2.1 *	23.0	114.9	-4.9 *	23.1	111.9	-6.1 *
200	90	60	80.3	293.9	13.7 *	81.3	289.8	12.3 *	80.0	280.3	10.3 *	80.1	275.8	8.9 *
200	90	70	78.3	291.7	13.4 *	79.3	287.2	11.9 *	77.9	277.0	10.2 *	78.0	272.5	8.9 *
200	90	80	76.3	289.2	13.1 *	77.2	284.3	11.5 *	75.7	273.2	10.0 *	75.8	268.7	8.9 *
200	90	90	74.2	286.3	12.8 *	75.1	281.0	11.1 *	73.6	268.9	9.9 *	73.7	264.4	8.3 *
200	90	100	72.2	283.0	12.5 *	73.0	277.2	10.7 *	71.4	259.0	8.3 *	71.5	254.5	7.6 *
200	90	110	70.1	279.2	12.1 *	70.9	273.0	10.4 *	69.1	253.3	7.0 *	69.2	249.8	6.2 *
200	90	120	68.0	275.1	11.6 *	68.7	268.4	10.1 *	66.8	247.1	6.2 *	66.9	243.6	5.0 *
200	90	130	65.8	270.5	11.2 *	66.5	263.3	9.9 *	64.4	240.2	4.0 *	64.5	237.7	2.8 *
200	90	140	63.6	265.5	10.8 *	64.2	257.7	9.8 *	62.0	234.2	2.8 *	62.1	231.7	1.6 *
200	90	150	61.4	259.9	10.4 *	61.9	251.6	9.3 *	59.9	229.2	1.6 *	60.0	226.7	0.4 *
200	90	160	59.1	253.8	10.1 *	59.5	244.8	9.3 *	57.9	226.7	0.4 *	58.0	224.2	-0.8 *
200	90	170	56.7	247.2	9.7 *	56.7	238.2	9.3 *	55.7	224.2	-0.8 *	55.8	221.7	-2.0 *


Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	8 Degrees			14 Degrees			24 Degrees		
			Boom Angle (deg)	Jib Pt Height (ft)	AB-A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB-A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB-A Capacity (1000 lbs)
190	70	150	57.3	224.5	15.8 *	59.7	222.7	15.4 *	61.8	218.8	12.2 *
190	70	160	54.6	217.4	14.5 *	57.0	215.5	14.5 *	59.1	212.8	11.5 *
190	70	170	51.8	209.6	14.0 *	54.2	207.6	13.7 *	56.2	205.8	10.1 *
190	70	180	48.6	200.9	13.2 *	51.3	198.8	13.0 *	53.3	197.5	9.1 *
190	70	190	45.6	191.3	12.5 *	48.2	189.1	12.5 *	50.1	184.0	8.5 *
190	70	200	42.7	180.5	11.8 *	44.9	178.2	11.8 *	46.8	173.4	7.8 *
190	70	210	39.3	168.5	11.2 *	41.5	165.9	10.9 *			
190	70	220	35.6	154.7	10.7 *	37.7	152.0	10.0 *			
190	70	230	31.4	138.8	9.8 *						
190	70	240	26.8	119.6	8.9 *						
190	90	60	80.0	283.7	13.8 *						
190	90	70	77.9	281.4	13.3 *	81.0	279.5	12.2 *	81.8	273.0	10.4 *
190	90	80	75.8	278.8	13.0 *	78.9	276.9	11.8 *	79.6	269.9	10.1 *
190	90	90	73.7	275.8	12.7 *	76.7	273.8	11.4 *	77.4	266.4	10.0 *
190	90	100	71.5	272.3	12.4 *	74.6	270.4	11.0 *	75.2	262.4	9.8 *
190	90	110	69.3	268.5	11.9 *	72.4	266.5	10.5 *	72.9	258.0	9.5 *
190	90	120	67.1	264.2	11.5 *	70.1	262.1	10.3 *	70.6	253.1	8.9 *
190	90	130	64.9	259.4	11.0 *	67.9	257.3	10.2 *	68.3	247.7	8.5 *
190	90	140	62.6	254.1	10.6 *	65.5	251.9	10.0 *	65.8	241.7	7.9 *
190	90	150	60.2	248.3	10.3 *	63.2	246.1	9.8 *	63.4	235.1	7.1 *
190	90	160	57.8	241.9	10.2 *	60.7	239.6	9.5 *	60.8	227.9	6.5 *
190	90	170	55.3	234.9	10.0 *	58.2	232.6	9.2 *	58.2	220.0	5.9 *
190	90	180	52.8	227.2	9.8 *	55.7	224.8	8.9 *	55.4	211.3	5.4 *
190	90	190	50.1	218.8	9.5 *	53.0	216.3	8.2 *	52.5	201.6	5.0 *
190	90	200	47.4	209.5	8.9 *	50.2	206.9	7.5 *	49.5	191.0	4.5 *
190	90	210	44.5	199.2	8.5 *	47.2	196.5	7.1 *	46.3	179.0	4.3 *
190	90	220	41.4	187.9	8.0 *	44.1	185.0	6.6 *			
190	90	230	38.1	175.1	7.6 *	40.7	172.0	6.2 *			
190	90	240	34.5	160.7	7.3 *	37.1	157.3	5.7 *			
190	90	250	30.6	144.0	7.0 *						
190	90	260	26.1	124.2	6.7 *						
200	30	40	81.5	236.7	40.0 *	80.3	234.0	40.0 *	81.4	232.4	40.0 *
200	30	50	79.0	234.8	40.0 *	77.7	231.7	40.0 *	78.9	230.1	40.0 *
200	30	60	76.5	232.6	40.0 *	75.1	229.0	40.0 *	76.3	227.3	40.0 *
200	30	70	73.9	229.8	40.0 *	72.5	225.7	40.0 *	73.6	224.0	40.0 *
200	30	80	71.3	226.5	40.0 *	69.9	221.9	40.0 *	71.0	220.2	38.5 *
200	30	90	68.7	222.8	40.0 *	67.2	217.6	38.6	68.3	215.9	36.5 *
200	30	100	66.0	218.5	38.1	64.4	212.7	33.8	65.5	210.9	34.2
200	30	110	63.3	213.6	33.3	61.6	207.2	29.5	62.6	205.4	29.8
200	30	120	60.5	208.1	29.1	58.7	201.0	25.9	59.7	199.1	26.2
200	30	130	57.6	201.9	25.7	55.7	194.1	22.9	56.6	192.1	23.2
200	30	140	54.6	195.0	22.7	52.6	186.3	20.4	53.5	184.3	20.6
200	30	150	51.4	187.3	20.2	49.3	177.6	18.2	50.2	175.5	18.4
200	30	160	48.2	178.7	18.0	45.8	167.8	16.2	46.7	165.6	16.4
200	30	170	44.7	169.0	16.1	42.1	156.7	14.5			
200	30	180	41.1	158.0	14.4	38.1	144.0	13.0			
200	30	190	37.1	145.4	13.0						
200	30	200	32.7	130.7	11.6						
200	30	210	27.7	113.1	10.4						
200	50	50	80.3	255.2	32.0 *						

28p1131

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	8 Degrees			15 Degrees			25 Degrees		
			Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)
180	80	210	42.2	184.2	8.5 *	45.0	181.4	7.3 *	47.3	175.7	4.8 *
180	80	220	38.5	171.8	8.1 *	41.8	168.8	6.8 *			
180	80	230	35.2	157.7	7.7 *	37.9	154.4	6.4 *			
180	80	240	31.2	141.4	7.4 *						
180	80	250	26.6	122.0	7.1 *						
180	30	40	81.1	226.5	40.0 *	79.8	223.8	40.0 *	81.0	222.2	40.0 *
180	30	50	78.5	224.8	40.0 *	77.1	221.4	40.0 *	78.3	219.8	40.0 *
180	30	60	75.9	222.2	40.0 *	74.4	218.5	40.0 *	75.6	216.9	40.0 *
180	30	70	73.2	219.3	40.0 *	71.7	215.1	40.0 *	72.9	213.4	40.0 *
180	30	80	70.5	215.9	40.0 *	68.9	211.1	40.0 *	70.1	209.4	40.0 *
180	30	90	67.7	212.0	40.0 *	66.1	206.5	40.0 *	67.2	204.8	37.8 *
180	30	100	64.9	207.4	40.0 *	63.2	201.4	38.9	64.2	199.6	36.6 *
180	30	110	62.0	202.3	38.4	60.2	195.5	34.1	61.2	193.7	34.5
180	30	120	59.0	196.4	33.7	57.1	188.9	29.8	58.1	187.0	30.1
180	30	130	55.9	189.9	29.5	53.9	181.5	26.3	54.8	179.5	26.5
180	30	140	52.7	182.5	26.0	50.5	173.2	23.3	51.4	171.1	23.5
180	30	150	49.3	174.2	23.1	46.9	163.8	20.7	47.8	161.5	20.9
180	30	160	45.8	164.9	20.6	43.1	153.0	18.5			
180	30	170	42.0	154.2	18.4	39.0	140.7	14.9			
180	30	180	38.0	142.0	16.5						
180	30	190	33.5	127.8	14.8						
180	30	200	28.4	110.6	12.0						
190	50	50	79.9	245.0	32.0 *	81.9	243.8	31.9 *			
190	50	60	77.5	242.8	32.0 *	79.4	241.6	31.3 *			
190	50	70	75.0	240.2	32.0 *	77.0	238.9	30.7 *	81.3	239.1	29.4 *
190	50	80	72.5	237.1	32.0 *	74.5	235.8	30.1 *	78.8	236.4	28.4 *
190	50	90	70.0	233.5	32.0 *	72.0	232.2	29.4 *	76.3	233.3	26.5 *
190	50	100	67.5	229.4	31.5 *	69.4	228.0	28.2 *	73.7	229.6	24.9 *
190	50	110	64.9	224.7	29.4 *	66.8	223.4	26.5 *	71.1	225.4	23.5 *
190	50	120	62.2	219.5	27.6 *	64.1	218.1	25.0 *	68.5	220.7	22.3 *
190	50	130	59.5	213.7	25.9 *	61.3	212.3	23.6 *	65.8	215.4	21.2 *
190	50	140	56.6	207.2	24.3 *	58.5	205.8	22.3 *	63.0	209.5	20.2 *
190	50	150	53.7	200.0	22.9 *	55.6	198.5	21.1 *	60.1	202.8	19.4 *
190	50	160	50.7	191.9	21.2	52.5	190.4	19.3	57.1	195.4	18.6 *
190	50	170	47.5	183.0	19.0	49.3	181.3	17.3	54.0	187.2	17.8 *
190	50	180	44.2	172.9	17.1	45.9	171.1	15.6	50.7	178.0	16.5 *
190	50	190	40.6	161.5	15.4	42.3	159.6	14.1	47.3	167.6	14.8 *
190	50	200	36.7	148.5	13.9	38.3	146.5	12.7			
190	50	210	32.4	133.4	12.6						
190	50	220	27.5	115.3	10.3						
190	70	50	81.0	265.3	21.8 *	81.4	261.7	20.3 *	81.6	256.0	18.4 *
190	70	60	78.8	263.3	21.5 *	79.1	259.2	19.9 *	79.2	253.1	18.0 *
190	70	70	76.6	260.9	21.1 *	76.8	256.4	19.4 *	76.9	249.8	17.1 *
190	70	80	74.3	258.0	20.8 *	74.5	253.1	19.0 *	74.5	246.0	16.1 *
190	70	90	72.0	254.7	20.4 *	72.2	249.3	18.5 *	72.1	241.7	15.2 *
190	70	100	69.7	251.0	20.0 *	69.8	245.1	18.1 *	69.6	236.8	14.4 *
190	70	110	67.3	246.8	19.5 *	67.4	240.3	17.7 *	67.1	231.5	13.8 *
190	70	120	64.9	242.0	19.0 *	64.9	235.0	16.4 *	64.5	225.5	13.2 *
190	70	130	62.4	236.8	18.0 *						
190	70	140	59.9	231.0	16.9 *						



Refer to all notes in front of the Crane Rating Manual before operating the machine.
Jib Angle to Boom

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	5 Degrees			15 Degrees			25 Degrees		
			Boom Angle (deg)	Jib Pt Height (ft)	AB-A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB-A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB-A Capacity (1000 lbs)
180	50	60	76.9	232.5	32.0 *	79.0	231.3	31.2 *	80.9	229.8	29.3 *
180	50	70	74.4	229.7	32.0 *	76.4	228.5	30.5 *	78.3	226.5	28.0 *
180	50	80	71.8	226.5	31.5 *	73.8	225.2	29.9 *	75.7	222.9	26.1 *
180	50	90	69.1	222.7	31.2 *	71.1	221.4	29.4 *	73.0	218.5	24.5 *
180	50	100	66.4	218.4	29.6 *	68.4	217.1	28.4 *	70.3	214.5	23.1 *
180	50	110	63.7	213.5	27.7 *	65.7	212.2	26.7 *	67.5	209.5	21.9 *
180	50	120	60.9	208.0	26.0 *	62.8	206.7	25.2 *	64.6	203.9	19.8 *
180	50	130	58.0	201.9	24.5 *	59.9	200.4	23.6 *	61.6	197.0	17.5 *
180	50	140	55.0	195.0	23.0 *	56.9	193.5	22.5 *	58.6	190.8	15.0 *
180	50	150	51.9	187.3	21.5 *	53.8	185.7	21.3 *	55.4	182.6	13.3 *
180	50	160	48.6	178.6	19.4 *	50.5	177.0	19.6 *	52.0	173.8	11.7 *
180	50	170	45.2	168.9	17.4 *	47.0	167.2	17.7 *	48.5	163.7	10.1 *
180	50	180	41.5	157.9	15.8 *	43.3	156.0	15.9 *			
180	50	190	37.5	145.3	14.3 *	39.3	143.3	14.4 *			
180	50	200	33.1	130.6	12.9 *						
180	50	210	28.1	113.0	11.7 *						
180	70	50	80.7	255.1	21.8 *	81.0	251.5	20.3 *	81.2	245.7	18.3 *
180	70	60	78.4	253.0	21.4 *	78.7	248.9	19.8 *	78.8	242.7	17.9 *
180	70	70	76.0	250.5	21.1 *	76.3	245.9	19.3 *	76.3	239.2	16.8 *
180	70	80	73.7	247.5	20.7 *	73.9	242.5	18.8 *	73.8	235.2	15.9 *
180	70	90	71.2	244.1	20.3 *	71.4	238.5	18.4 *	71.3	230.7	15.0 *
180	70	100	68.8	240.2	19.8 *	68.9	234.1	18.0 *	68.7	225.6	14.2 *
180	70	110	66.3	235.8	19.3 *	66.4	229.1	17.6 *	66.1	220.0	13.5 *
180	70	120	63.8	230.8	18.8 *	63.8	223.5	17.1 *	63.3	213.7	12.9 *
180	70	130	61.2	225.3	18.0 *	61.1	217.3	16.4 *	60.5	206.7	12.4 *
180	70	140	58.5	219.2	16.9 *	58.3	210.5	15.5 *	57.6	198.9	11.5 *
180	70	150	55.8	212.4	15.9 *	55.4	202.9	14.6 *	54.5	190.3	10.5 *
180	70	160	52.9	204.8	14.9 *	52.4	194.4	13.8 *	51.3	180.6	9.8 *
180	70	170	50.0	196.5	14.1 *	49.3	185.0	13.1 *	47.9	169.8	8.9 *
180	70	180	46.9	187.1	13.3 *	46.0	174.4	12.4 *			
180	70	190	43.6	176.7	12.6 *	42.4	162.5	11.8 *			
180	70	200	40.1	165.0	11.9 *	38.5	148.9	11.3 *			
180	70	210	36.3	151.6	11.3 *						
180	70	220	32.1	136.1	10.8 *						
180	70	230	27.3	117.6	10.1 *						
180	90	50	81.7	275.4	13.9 *	80.6	269.3	12.2 *	81.5	262.7	10.4 *
180	90	60	79.6	273.5	13.6 *	78.4	266.5	11.7 *	79.2	259.5	10.3 *
180	90	70	77.4	271.1	13.3 *	76.2	263.3	11.3 *	76.9	255.8	10.1 *
180	90	80	75.3	268.4	12.9 *	74.0	259.7	10.8 *	74.6	251.7	9.9 *
180	90	90	73.0	265.3	12.6 *	71.7	255.6	10.4 *	72.2	247.1	9.8 *
180	90	100	70.8	261.7	12.2 *	69.3	251.1	10.3 *	69.8	241.9	9.6 *
180	90	110	68.5	257.6	11.8 *	67.0	246.1	10.1 *	67.3	236.2	8.9 *
180	90	120	66.2	253.1	11.3 *	64.5	240.5	9.9 *	64.8	229.9	8.0 *
180	90	130	63.9	248.1	10.8 *	62.0	234.3	9.8 *	62.2	223.0	7.4 *
180	90	140	61.5	242.6	10.4 *	59.5	227.5	9.6 *	59.5	215.4	6.6 *
180	90	150	59.0	236.5	10.2 *	56.8	220.0	9.4 *	56.7	207.0	6.1 *
180	90	160	56.5	229.8	9.9 *	54.1	211.8	9.1 *	53.7	197.6	5.7 *
180	90	170	53.8	222.4	9.7 *	51.2	202.7	8.5 *	50.6	187.3	5.1 *
180	90	180	51.1	214.2	9.5 *	48.2	192.6	7.9 *			
180	90	190	48.3	205.2	9.0 *						
180	90	200	45.3	195.3							

28p1131

ON TIRE
CAPACITIES

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	5 Degrees			15 Degrees			25 Degrees		
			Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)
170	70	110	65.3	224.7	19.1 *	68.0	223.0	17.8 *	70.4	219.6	14.7 *
170	70	120	62.6	219.5	18.6 *	65.3	217.8	17.4 *	67.7	214.3	14.0 *
170	70	130	59.8	213.7	18.1 *	62.5	211.9	16.9 *	64.9	208.3	13.3 *
170	70	140	57.0	207.2	17.0 *	59.7	205.3	16.3 *	62.0	201.7	12.7 *
170	70	150	54.1	199.9	15.9 *	56.7	198.0	15.4 *	59.0	194.2	12.2 *
170	70	160	51.1	191.9	14.1 *	53.7	189.9	14.6 *	55.9	185.9	11.7 *
170	70	170	47.9	182.9	13.3 *	50.4	180.8	13.9 *	52.6	176.6	10.8 *
170	70	180	44.6	172.8	12.6 *	47.0	170.6	13.2 *	49.1	166.1	10.0 *
170	70	200	41.0	161.5	12.0 *	43.4	159.1	12.5 *	45.3	154.3	9.1 *
170	70	210	37.1	148.5	11.4 *	39.5	145.9	11.4 *			
170	70	220	32.8	133.4	10.9 *	35.1	130.4				
170	90	50	81.4	265.3	13.9 *	80.3	259.0	12.1 *			
170	90	60	79.2	263.3	13.5 *	78.0	256.1	11.6 *			
170	90	70	76.9	260.8	13.2 *	75.7	252.8	11.2 *	81.1	252.3	10.4 *
170	90	80	74.7	258.0	12.9 *	73.3	249.0	10.7 *	78.8	249.0	10.2 *
170	90	90	72.4	254.7	12.5 *	70.9	244.8	10.4 *	76.4	245.2	10.1 *
170	90	100	70.0	250.9	12.1 *	68.5	240.0	10.2 *	73.9	240.8	9.9 *
170	90	110	67.7	246.7	11.6 *	66.0	234.7	10.0 *	71.5	236.0	9.7 *
170	90	120	65.3	242.0	11.1 *	63.4	228.8	9.9 *	68.9	230.6	9.6 *
170	90	130	62.8	236.8	10.6 *	60.8	222.3	9.7 *	66.3	224.6	9.0 *
170	90	140	60.3	230.9	10.3 *	58.1	215.2	9.5 *	63.6	218.0	8.3 *
170	90	150	57.7	224.5	10.2 *	55.3	207.2	9.3 *	60.9	210.7	7.5 *
170	90	160	55.0	217.4	9.8 *	52.4	198.4	9.1 *	58.0	202.5	6.9 *
170	90	170	52.2	209.6	9.6 *	49.3	188.7	8.7 *	55.0	193.5	6.4 *
170	90	180	49.3	200.9	9.4 *	46.0	177.8	8.2 *	51.8	183.5	5.8 *
170	90	190	46.3	191.2	9.0 *	42.5	165.5	7.6 *	48.5	172.3	5.3 *
170	90	200	43.1	180.5	8.6 *	38.8	151.5	7.0 *			
170	90	210	39.6	168.4	8.2 *						
170	90	220	35.9	154.7	7.8 *						
170	90	230	31.8	138.8	7.5 *						
170	90	240	27.1	119.8							
180	30	40	80.7	216.4	40.0 *	79.3	213.6	40.0 *	80.6	212.0	40.0 *
180	30	50	78.0	214.4	40.0 *	76.5	211.1	40.0 *	77.8	209.4	40.0 *
180	30	60	75.2	211.9	40.0 *	73.7	208.0	40.0 *	74.9	206.4	40.0 *
180	30	70	72.4	208.8	40.0 *	70.8	204.4	40.0 *	72.0	202.7	39.4 *
180	30	80	69.5	205.2	40.0 *	67.9	200.2	40.0 *	69.0	198.5	37.1 *
180	30	90	66.6	201.0	40.0 *	64.9	195.4	39.2	66.0	193.6	36.6 *
180	30	100	63.6	196.2	38.8	61.8	189.9	34.4	62.9	188.1	34.7
180	30	110	60.5	190.8	34.0	58.6	183.6	30.1	59.7	181.8	30.4
180	30	120	57.3	184.6	29.8	55.3	176.6	26.6	56.3	174.7	26.8
180	30	130	54.0	177.6	26.4	51.8	168.6	21.0	52.8	166.6	23.8
180	30	140	50.6	169.6	23.4	48.1	159.6	18.8	49.1	157.4	21.2
180	30	150	47.0	160.7	20.9	44.3	149.2	16.9	45.1	146.9	19.0
180	30	160	43.1	150.4	18.7	40.0	137.3	15.2			
180	30	170	38.9	138.6	16.8	35.4	123.4				
180	30	180	34.3	124.8	15.2						
180	30	190	29.1	108.2	13.7						
50	40	82.0	236.6	32.0 *	81.5	233.6	31.8 *				
50	50	79.4	234.8	32.0 *							

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	8 Degrees			14 Degrees			24 Degrees		
			Boom Angle (deg)	Jib Height (ft)	ARE Capacity (1000 lbs)	Boom Angle (deg)	Jib Height (ft)	ARE Capacity (1000 lbs)	Boom Angle (deg)	Jib Height (ft)	ARE Capacity (1000 lbs)
160	90	130	61.6	225.3	10.8 *	64.9	223.2	10.6 *	68.0	219.2	8.6 *
160	90	140	58.9	219.1	10.9 *	62.2	217.0	9.8 *	65.2	212.5	9.4 *
160	90	150	56.2	212.3	10.1 *	59.4	210.2	9.6 *	62.4	205.8	8.4 *
160	90	160	53.3	204.8	9.9 *	56.6	202.5	9.4 *	59.4	199.0	7.8 *
160	90	170	50.4	196.4	9.7 *	53.6	194.1	9.2 *	56.4	190.3	7.0 *
160	90	180	47.3	187.1	9.4 *	50.4	184.6	9.0 *	53.1	179.9	6.4 *
160	90	190	44.0	176.7	9.0 *	47.1	174.1	8.7 *	49.7	168.7	5.9 *
160	90	200	40.5	165.0	8.6 *	43.5	162.1	8.3 *	46.0	156.4	5.5 *
160	90	210	36.7	151.6	8.2 *	39.7	148.5	7.9 *			
160	90	220	32.5	136.1	7.7 *	35.4	132.6	7.4 *			
160	90	230	27.7	117.5							
170	30	35	81.7	207.1	40.0 *						
170	30	40	80.3	206.2	40.0 *	81.7	205.4	40.0 *			
170	30	50	77.4	204.1	40.0 *	78.8	203.3	40.0 *	80.1	201.7	40.0 *
170	30	60	74.4	201.5	40.0 *	75.8	200.7	40.0 *	77.1	199.1	40.0 *
170	30	70	71.5	196.3	40.0 *	72.8	197.4	40.0 *	74.1	195.8	40.0 *
170	30	80	68.4	194.5	40.0 *	69.8	193.6	40.0 *	71.0	192.0	38.7 *
170	30	90	65.3	190.0	40.0 *	66.7	189.2	40.0 *	67.9	187.5	36.4 *
170	30	100	62.1	184.9	39.1	63.5	184.1	39.5	64.7	182.3	36.6 *
170	30	110	58.9	179.1	34.4	60.2	178.2	34.7	61.3	176.4	35.0
170	30	120	55.5	172.5	30.2	56.8	171.5	30.4	57.9	169.6	30.7
170	30	130	51.9	164.9	26.7	53.2	163.9	26.9	54.3	161.9	27.1
170	30	140	48.2	156.3	23.8	49.4	155.3	23.9	50.5	153.2	24.1
170	30	150	44.2	146.5	21.3	45.4	145.4	21.4	46.4	143.1	21.5
170	30	160	39.9	135.1	19.1	41.1	133.9	19.1			
170	30	170	35.2	121.7	17.2	36.3	120.4	17.2			
170	30	180	29.8	105.6	15.5						
170	50	40	81.6	226.5	32.0 *						
170	50	50	79.0	224.6	32.0 *	81.1	223.4	31.7 *			
170	50	60	76.3	222.2	32.0 *	78.5	221.0	31.1 *	80.5	218.5	29.3 *
170	50	70	73.6	219.3	32.0 *	75.8	218.0	30.4 *	77.8	215.6	27.6 *
170	50	80	70.9	215.9	31.7 *	73.0	214.6	29.7 *	75.0	212.1	25.7 *
170	50	90	68.1	211.9	31.0 *	70.2	210.6	29.2 *	72.2	208.1	24.1 *
170	50	100	65.3	207.4	29.7 *	67.4	206.1	28.5 *	69.3	203.4	22.7 *
170	50	110	62.4	202.2	27.8 *	64.5	200.9	26.8 *	66.3	198.2	21.5 *
170	50	120	59.4	196.4	26.1 *	61.5	195.0	25.3 *	63.3	192.2	20.4 *
170	50	130	56.3	189.8	24.5 *	58.3	188.4	23.9 *	60.1	185.5	19.4 *
170	50	140	53.1	182.5	23.1 *	55.1	181.0	22.6 *	56.8	178.0	18.6 *
170	50	150	49.8	174.2	21.8 *	51.7	172.6	21.4 *	53.4	169.4	17.9 *
170	50	160	46.2	164.8	19.7	48.2	163.1	19.9	49.7	159.8	17.3 *
170	50	170	42.5	154.2	17.8	44.4	152.4	18.0	45.8	148.8	16.7 *
170	50	180	38.4	142.0	16.1	40.2	140.0	16.3			
170	50	190	33.9	127.7	14.6	35.7	125.5	14.7			
170	50	200	28.8	110.5	13.3						
170	70	50	80.3	244.9	21.7 *	80.7	241.2	20.2 *			
170	70	60	77.9	242.8	21.3 *	78.2	238.5	19.7 *	80.8	235.4	18.3 *
170	70	70	75.4	240.1	21.0 *	75.7	235.4	19.2 *	78.3	232.2	17.8 *
170	70	80	72.9	237.0	20.6 *	73.2	231.8	18.7 *	75.7	228.6	16.6 *
170	70	90	70.4	233.4	20.1 *	70.6	227.7	18.2 *	73.1	224.4	15.6 *
170	70	100	67.9	229.3	19.6 *						

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	8 Degrees			15 Degrees			25 Degrees		
			Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)
160	30	80	63.9	178.9	40.0 *	65.4	178.0	40.0 *	66.6	176.3	36.6 *
160	30	100	60.5	173.5	39.5	62.0	172.6	39.8	63.2	170.8	36.6 *
160	30	110	57.0	167.2	34.7	58.4	166.3	35.0	59.6	164.4	35.3
160	30	120	53.4	160.1	30.5	54.7	159.1	30.7	55.9	157.2	31.0
160	30	130	49.5	151.9	27.0	50.9	150.8	27.2	52.0	148.8	27.4
160	30	140	45.4	142.4	24.1	46.7	141.3	24.2	47.8	139.2	24.4
160	30	150	41.0	131.5	21.6	42.3	130.3	21.7			
160	30	160	36.1	118.6	19.4						
160	30	170	30.6	103.0	17.5	37.4	117.3	19.4			
160	50	40	81.2	216.3	32.0 *						
160	50	50	78.4	214.3	32.0 *						
160	50	60	75.6	211.6	32.0 *	80.7	213.1	31.6 *			
160	50	70	72.6	208.8	32.0 *	77.9	210.6	30.9 *			
160	50	80	70.0	205.2	31.4 *	75.1	207.5	30.2 *			
160	50	90	67.0	201.0	30.7 *	72.2	203.9	29.5 *	80.0	208.2	29.2 *
160	50	100	64.0	196.2	29.8 *	69.2	199.7	29.1 *	77.1	205.1	27.2 *
160	50	110	61.0	190.7	27.9 *	66.2	194.9	28.6 *	74.2	201.4	25.2 *
160	50	120	57.8	184.5	26.2 *	63.1	189.4	26.9 *	71.2	197.2	23.6 *
160	50	130	54.5	177.5	24.6 *	59.9	183.1	25.4 *	68.2	192.3	22.2 *
160	50	140	51.0	169.6	23.2 *	56.6	176.1	24.0 *	65.0	186.7	21.0 *
160	50	150	47.4	160.6	21.9 *	53.1	168.1	22.6 *	61.8	180.4	19.9 *
160	50	160	43.5	150.3	20.1	49.4	159.0	21.5 *	58.4	173.2	19.0 *
160	50	170	39.4	138.5	18.2	45.5	148.6	20.3	54.9	165.0	18.2 *
160	50	180	34.8	124.7	16.5	41.3	136.7	18.3	51.1	155.7	17.5 *
160	50	190	29.5	108.1	15.0	36.6	122.6	16.6	47.1	145.1	16.9 *
160	70	50	79.9	234.8	21.6 *						
160	70	60	77.3	232.5	21.3 *						
160	70	70	74.8	229.7	20.9 *	80.2	230.9	20.1 *			
160	70	80	72.2	226.4	20.5 *	77.7	228.1	19.6 *			
160	70	90	69.5	222.7	20.0 *	75.1	224.9	19.1 *			
160	70	100	66.9	218.4	19.4 *	72.4	221.1	18.5 *	80.4	225.1	18.2 *
160	70	110	64.1	213.5	18.9 *	69.7	216.7	18.1 *	77.7	221.7	17.5 *
160	70	120	61.3	208.0	18.3 *	66.9	211.8	17.6 *	75.1	217.9	16.4 *
160	70	130	58.4	201.8	17.9 *	64.1	206.3	17.2 *	72.3	213.5	15.4 *
160	70	140	55.4	194.9	17.0 *	61.2	200.1	16.7 *	69.5	208.5	14.5 *
160	70	150	52.3	187.2	16.0 *	58.1	193.1	15.8 *	66.6	202.8	13.7 *
160	70	160	49.0	178.6	15.0 *	55.0	185.3	15.0 *	63.6	196.5	13.0 *
160	70	170	45.6	168.8	14.2 *	51.7	176.5	14.2 *	60.5	189.4	12.4 *
160	70	180	41.9	157.8	13.4 *	48.2	166.7	13.5 *	57.3	181.4	11.9 *
160	70	190	37.9	145.2	12.7 *	44.5	155.5	12.9 *	54.0	172.5	11.4 *
160	70	200	33.6	130.5	12.1 *	40.4	142.7	12.4 *	50.4	162.4	11.0 *
160	70	210	28.6	112.9	11.5 *	36.0	127.7	12.0 *	46.5	150.9	10.4 *
160	90	50	81.1	255.1	13.8 *						
160	90	60	78.8	253.0	13.5 *						
160	90	70	76.4	250.5	13.1 *						
160	90	80	74.0	247.5	12.8 *	79.9	248.6	12.0 *			
160	90	90	71.6	244.1	12.4 *	77.5	245.7	11.5 *			
160	90	100	69.2	240.2	11.9 *	75.0	242.2	11.1 *	80.7	242.0	10.4 *
160	90	110	66.7	235.7	11.4 *	72.6	238.2	10.6 *	78.3	238.5	10.2 *
160	90	120	64.2	230.8	10.9 *	70.1	233.8	10.3 *	75.8	234.4	10.0 *
						67.5	228.8	10.1 *	73.2	229.9	9.9 *
									70.6	224.8	9.7 *

Refer to all notes in front of the Crane Rating Manual before operating the machine.											
Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	8 Degrees		15 Degrees		22 Degrees		30 Degrees		AS-A Capacity (1000 lbs)
			Boom Angle (deg)	Jib Pt Height (ft)	AS-A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AS-A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	
150	50	90	65.8	180.0	30.4 *	68.1	188.9	28.0 *	70.2	190.5	25.1 *
150	50	100	62.8	184.8	29.6 *	64.9	183.6	28.6 *	67.0	181.5	21.7 *
150	50	110	59.4	179.1	27.9 *	61.6	177.7	28.5 *	63.8	171.5	20.5 *
150	50	120	56.0	172.4	26.2 *	58.2	171.0	28.7 *	60.1	168.3	19.5 *
150	50	130	52.4	164.8	24.6 *	54.6	163.4	23.2 *	56.5	160.8	18.6 *
150	50	140	48.7	156.3	23.2 *	50.8	154.7	21.9 *	52.6	151.6	17.4 *
150	50	150	44.7	146.4	22.0 *	46.8	144.7	20.8 *	48.5	141.4	17.0 *
150	50	160	40.4	135.0	20.4 *	42.5	133.2	19.8 *			
150	50	170	35.7	121.7	18.5 *	37.6	119.6	18.6 *			
150	50	180	30.3	105.5	16.8 *						
150	70	50	79.4	224.5	21.6 *	79.8	220.6	20.0 *			
150	70	60	76.8	222.1	21.2 *	77.1	217.7	19.5 *	79.9	214.7	18.1 *
150	70	70	74.1	219.2	20.8 *	74.3	214.3	18.9 *	77.2	211.2	17.3 *
150	70	80	71.3	215.8	20.3 *	71.5	210.3	18.4 *	74.3	207.1	16.1 *
150	70	90	68.6	211.9	19.8 *	68.7	205.7	17.9 *	71.4	202.5	15.1 *
150	70	100	65.7	207.3	19.2 *	65.8	200.5	17.5 *	68.4	197.2	14.2 *
150	70	110	62.8	202.2	18.6 *	62.8	194.6	17.0 *	65.4	191.2	13.4 *
150	70	120	59.9	196.3	18.1 *	59.6	188.0	16.3 *	62.2	184.4	12.8 *
150	70	130	56.8	189.8	17.6 *	56.4	180.6	15.3 *	58.9	176.8	12.2 *
150	70	140	53.6	182.4	17.0 *	53.0	172.2	14.5 *	55.4	168.3	11.7 *
150	70	150	50.2	174.1	16.0 *	49.4	162.7	13.8 *	51.8	158.5	11.2 *
150	70	160	46.7	164.7	15.0 *	45.6	151.9	13.1 *	47.8	147.4	10.8 *
150	70	170	42.9	154.1	14.2 *	41.5	139.5	12.6 *			
150	70	180	38.9	141.9	13.4 *	36.9	124.9	12.1 *			
150	70	190	34.4	127.6	12.8 *						
150	70	200	29.2	110.5	12.2 *						
150	90	50	80.7	244.9	13.8 *	81.9	241.0	12.4 *			
150	90	60	78.3	242.7	13.4 *	79.4	238.3	11.9 *			
150	90	70	75.8	240.1	13.0 *	76.9	235.2	11.4 *	80.3	231.6	10.3 *
150	90	80	73.4	237.0	12.7 *	74.4	231.5	10.9 *	77.7	227.9	10.2 *
150	90	90	70.8	233.4	12.2 *	71.8	227.4	10.4 *	75.1	223.7	10.0 *
150	90	100	68.3	229.3	11.7 *	69.2	222.7	10.3 *	72.4	218.9	9.8 *
150	90	110	65.7	224.7	11.2 *	66.5	217.5	10.1 *	69.7	213.6	9.6 *
150	90	120	63.0	219.5	10.7 *	63.7	211.6	9.9 *	66.9	207.6	9.4 *
150	90	130	60.3	213.6	10.3 *	60.9	205.0	9.7 *	64.0	200.9	8.9 *
150	90	140	57.5	207.1	10.1 *	57.9	197.7	9.5 *	61.0	193.4	8.5 *
150	90	150	54.5	199.9	9.9 *	54.9	189.6	9.3 *	57.8	185.1	8.0 *
150	90	160	51.5	191.9	9.7 *	51.6	180.5	9.1 *	54.5	175.7	7.3 *
150	90	170	48.3	182.9	9.5 *	48.2	170.3	8.8 *	51.0	165.2	6.6 *
150	90	180	45.0	172.8	9.3 *	44.6	158.7	8.4 *	47.2	153.2	6.2 *
150	90	190	41.4	161.4	9.0 *	40.6	145.5	8.0 *			
150	90	200	37.5	148.4	8.7 *	36.2	130.0	7.6 *			
150	90	210	33.2	133.3	8.3 *						
150	90	220	28.3	115.2	7.8 *						
160	30	35	81.3	197.0	40.0 *	81.2	195.3	40.0 *			
160	30	40	79.7	196.1	40.0 *	78.2	193.0	40.0 *	79.6	191.5	40.0 *
160	30	50	76.7	193.8	40.0 *	75.1	190.2	40.0 *	76.4	188.6	40.0 *
160	30	60	73.6	191.0	40.0 *	71.9	186.8	40.0 *	73.2	185.2	40.0 *
160	30	70	70.4	187.6	40.0 *	68.7	182.8	40.0 *	70.0	181.1	37.9 *
160	30	80	67.2	183.6	40.0 *						

28p1131

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	5 Degrees			15 Degrees			25 Degrees		
			Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)	Boom Angle (deg)	Jib Pt Height (ft)	AB+A Capacity (1000 lbs)
140	70	60	76.1	211.8	21.1 *	79.3	210.3	19.9 *	79.4	204.2	18.0 *
140	70	70	73.3	208.7	20.6 *	76.4	207.2	19.3 *	76.5	200.6	17.0 *
140	70	80	70.4	205.1	20.1 *	73.6	203.6	18.8 *	73.5	196.3	15.8 *
140	70	90	67.5	201.0	19.5 *	70.8	199.4	18.2 *	70.4	191.3	14.8 *
140	70	100	64.5	196.2	19.0 *	67.8	194.5	17.7 *	67.3	185.7	13.9 *
140	70	110	61.4	190.7	18.4 *	64.5	189.0	17.3 *	64.0	179.3	13.2 *
140	70	120	58.2	184.5	17.9 *	61.3	182.8	16.7 *	60.6	172.1	12.5 *
140	70	130	54.9	177.5	17.3 *	57.9	175.7	15.8 *	57.0	163.9	11.9 *
140	70	140	51.5	169.5	16.8 *	54.5	167.7	14.9 *	53.3	154.6	11.4 *
140	70	150	47.9	160.5	16.0 *	50.8	158.6	14.1 *	49.2	143.9	11.0 *
140	70	160	44.0	150.3	15.0 *	46.9	148.2	13.3 *			
140	70	170	39.8	138.5	14.2 *	42.6	136.2	12.7 *			
140	70	180	35.2	124.7	13.5 *	37.9	122.1	12.2 *			
140	70	190	30.0	108.0	12.9 *						
140	90	50	80.3	234.7	13.7 *						
140	90	60	77.8	232.4	13.3 *	81.5	230.7	12.4 *			
140	90	70	75.2	229.7	12.9 *	78.9	227.9	11.8 *			
140	90	80	72.6	226.4	12.5 *	76.3	224.6	11.3 *	79.9	221.1	10.3 *
140	90	90	70.0	222.7	12.0 *	73.7	220.8	10.8 *	77.2	217.2	10.1 *
140	90	100	67.3	218.3	11.5 *	71.0	216.5	10.4 *	74.4	212.8	9.9 *
140	90	110	64.5	213.5	11.0 *	68.2	211.6	10.2 *	71.6	207.8	9.7 *
140	90	120	61.7	208.0	10.4 *	65.3	206.0	10.0 *	68.7	202.1	9.5 *
140	90	130	58.8	201.8	10.2 *	62.4	199.8	9.8 *	65.7	195.8	9.2 *
140	90	140	55.8	194.9	10.0 *	59.4	192.8	9.6 *	62.6	188.7	8.7 *
140	90	150	52.7	187.2	9.8 *	56.2	185.0	9.4 *	59.4	180.7	8.3 *
140	90	160	49.5	178.5	9.6 *	52.9	176.3	9.1 *	56.0	171.7	7.9 *
140	90	170	46.0	168.8	9.4 *	49.4	166.4	8.9 *	52.4	161.5	7.4 *
140	90	180	42.3	157.8	9.1 *	45.7	155.2	8.5 *	48.5	149.9	6.9 *
140	90	190	38.4	145.2	8.8 *	41.7	142.3	8.1 *			
140	90	200	34.0	130.5	8.3 *	37.2	127.3	7.7 *			
140	90	210	29.0	112.8	7.8 *						
150	30	35	80.8	186.8	40.0 *						
150	30	40	79.2	185.9	40.0 *	80.7	185.1	40.0 *			
150	30	50	75.9	183.5	40.0 *	77.5	182.7	40.0 *	79.0	181.1	40.0 *
150	30	60	72.7	180.5	40.0 *	74.2	179.7	40.0 *	75.6	178.1	40.0 *
150	30	70	69.3	176.9	40.0 *	70.9	176.1	40.0 *	72.2	174.5	39.7 *
150	30	80	65.9	172.6	40.0 *	67.4	171.8	40.0 *	68.8	170.1	37.1 *
150	30	90	62.4	167.6	40.0 *	63.9	166.7	40.0 *	65.2	165.0	36.7 *
150	30	100	58.7	161.8	39.8	60.2	160.9	40.0 *	61.5	159.1	36.7 *
150	30	110	55.0	155.0	35.0	56.4	154.1	35.3	57.6	152.2	35.2 *
150	30	120	51.0	147.3	30.8	52.4	146.3	31.0	53.6	144.3	31.3
150	30	130	46.7	138.3	27.4	48.1	137.2	27.5	49.3	135.1	27.7
150	30	140	42.2	127.8	24.4	43.5	126.6	24.5			
150	30	150	37.2	115.4	21.9	38.5	114.1	22.0			
150	30	160	31.5	100.3	19.8						
150	50	40	80.7	206.2	32.0 *						
150	50	50	77.8	204.1	32.0 *	80.2	202.9	31.5 *			
150	50	60	74.9	201.4	32.0 *	77.3	200.2	30.8 *	79.5	197.9	29.0 *
150	50	70	71.9	198.2	31.9 *	74.3	197.0	30.0 *	76.5	194.6	26.7 *
150	50	80	68.9	194.4	31.2 *	71.2	193.2	29.4 *	73.4	190.7	24.8 *

HC-268

Refer to all notes in back of this manual relating to the use of the following tables.											
Jib Angle to Boom											
Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	Boom Angle (deg)	Jib Angle (deg)	Capacity (tons)	Boom Angle (deg)	Jib Angle (deg)	Capacity (tons)	Boom Angle (deg)	Jib Angle (deg)	Capacity (tons)
120	30	30	80.9	157.2	40.0	80.9	157.2	40.0	80.9	157.2	40.0
120	30	35	79.9	156.3	40.0	79.9	156.3	40.0	79.9	156.3	40.0
120	30	40	77.9	155.3	40.0	77.9	155.3	40.0	77.9	155.3	40.0
120	30	45	75.9	154.3	40.0	75.9	154.3	40.0	75.9	154.3	40.0
120	30	50	73.9	153.2	40.0	73.9	153.2	40.0	73.9	153.2	40.0
120	30	55	71.9	152.2	40.0	71.9	152.2	40.0	71.9	152.2	40.0
120	30	60	69.9	151.1	40.0	69.9	151.1	40.0	69.9	151.1	40.0
120	30	65	67.9	150.0	40.0	67.9	150.0	40.0	67.9	150.0	40.0
120	30	70	65.9	148.9	40.0	65.9	148.9	40.0	65.9	148.9	40.0
120	30	75	63.9	147.8	40.0	63.9	147.8	40.0	63.9	147.8	40.0
120	30	80	61.9	146.7	40.0	61.9	146.7	40.0	61.9	146.7	40.0
120	30	85	59.9	145.6	40.0	59.9	145.6	40.0	59.9	145.6	40.0
120	30	90	57.9	144.5	40.0	57.9	144.5	40.0	57.9	144.5	40.0
120	30	100	51.9	142.4	40.0	51.9	142.4	40.0	51.9	142.4	40.0
120	30	110	46.9	140.3	40.0	46.9	140.3	40.0	46.9	140.3	40.0
120	30	120	41.9	138.2	40.0	41.9	138.2	40.0	41.9	138.2	40.0
120	30	130	36.9	136.1	40.0	36.9	136.1	40.0	36.9	136.1	40.0
120	30	140	31.9	134.0	40.0	31.9	134.0	40.0	31.9	134.0	40.0
120	30	150	26.9	131.9	40.0	26.9	131.9	40.0	26.9	131.9	40.0
120	30	160	21.9	129.8	40.0	21.9	129.8	40.0	21.9	129.8	40.0
120	50	35	80.8	176.8	32.0	80.8	176.8	32.0	80.8	176.8	32.0
120	50	40	79.1	175.8	32.0	79.1	175.8	32.0	79.1	175.8	32.0
120	50	45	77.5	174.8	32.0	77.5	174.8	32.0	77.5	174.8	32.0
120	50	50	75.7	173.7	32.0	75.7	173.7	32.0	75.7	173.7	32.0
120	50	55	72.2	172.6	32.0	72.2	172.6	32.0	72.2	172.6	32.0
120	50	60	68.8	171.5	31.1	71.4	169.9	29.4	70.1	167.9	27.5
120	50	65	65.0	169.9	30.2	67.7	167.3	29.0	66.3	165.3	25.1
120	50	70	61.2	168.1	29.4	63.9	164.8	27.9	62.2	162.9	23.2
120	50	75	57.3	166.2	28.9	59.9	162.5	26.6	58.0	160.9	21.5
120	50	80	53.1	164.5	27.7	55.7	160.1	25.1	53.5	158.3	19.0
120	50	85	48.8	162.9	26.0	51.3	157.4	23.7	49.6	155.6	17.2
120	50	90	44.0	161.2	24.5	46.5	154.7	22.2	44.8	152.9	15.6
120	50	100	38.9	159.5	22.7	41.3	152.0	20.7	39.6	150.2	14.0
120	50	110	33.0	157.8	21.2	35.3	149.3	19.2	33.0	147.5	12.4
120	50	120	25.9	156.1	19.9	27.9	146.6	17.7	25.9	144.8	10.8
120	70	40	80.8	196.0	21.8	80.8	196.0	21.8	80.8	196.0	21.8
120	70	50	77.7	193.7	21.3	77.7	193.7	21.3	77.7	193.7	21.3
120	70	60	74.6	191.0	20.8	74.6	191.0	20.8	74.6	191.0	20.8
120	70	70	71.5	187.5	20.3	71.5	187.5	20.3	71.5	187.5	20.3
120	70	80	68.3	183.5	19.7	68.3	183.5	19.7	68.3	183.5	19.7
120	70	90	65.0	178.8	19.0	65.0	178.8	19.0	65.0	178.8	19.0
120	70	100	61.6	173.4	18.4	61.6	173.4	18.4	61.6	173.4	18.4
120	70	110	58.1	167.1	17.8	58.1	167.1	17.8	58.1	167.1	17.8
120	70	120	54.4	160.0	17.2	54.4	160.0	17.2	54.4	160.0	17.2
120	70	130	50.5	151.8	16.6	50.5	151.8	16.6	50.5	151.8	16.6
120	70	140	46.4	142.3	16.0	46.4	142.3	16.0	46.4	142.3	16.0
120	70	150	42.0	131.4	15.3	42.0	131.4	15.3	42.0	131.4	15.3
120	70	160	37.2	118.5	14.7	37.2	118.5	14.7	37.2	118.5	14.7
120	70	170	31.6	102.8	13.8	31.6	102.8	13.8	31.6	102.8	13.8
120	90	50	79.4	214.3	13.6	79.4	214.3	13.6	79.4	214.3	13.6
120	90	60	76.6	211.8	13.1	76.6	211.8	13.1	76.6	211.8	13.1
120	90	70	73.8	208.7	12.7	73.8	208.7	12.7	73.8	208.7	12.7
120	90	80	70.9	205.1	12.2	70.9	205.1	12.2	70.9	205.1	12.2
120	90	90	68.0	200.9	11.6	68.0	200.9	11.6	68.0	200.9	11.6
120	90	100	65.0	196.1	11.0	65.0	196.1	11.0	65.0	196.1	11.0
120	90	110	61.9	190.7	10.4	61.9	190.7	10.4	61.9	190.7	10.4
120	90	120	58.7	184.5	10.2	58.7	184.5	10.2	58.7	184.5	10.2
120	90	130	55.5	177.8	9.6	55.5	177.8	9.6	55.5	177.8	9.6
120	90	140	52.3	170.6	9.0	52.3	170.6	9.0	52.3	170.6	9.0
120	90	150	49.1	163.0	8.4	49.1	163.0	8.4	49.1	163.0	8.4
120	90	160	45.9	155.0	7.8	45.9	155.0	7.8	45.9	155.0	7.8
120	90	170	42.7	146.6	7.2	42.7	146.6	7.2	42.7	146.6	7.2
120	90	180	39.5	137.9	6.6	39.5	137.9	6.6	39.5	137.9	6.6
120	90	190	36.3	128.9	6.0	36.3	128.9	6.0	36.3	128.9	6.0
120	90	200	33.1	119.6	5.4	33.1	119.6	5.4	33.1	119.6	5.4
120	90	210	29.9	110.1	4.8	29.9	110.1	4.8	29.9	110.1	4.8
120	90	220	26.7	100.4	4.2	26.7	100.4	4.2	26.7	100.4	4.2
120	90	230	23.5	90.6	3.6	23.5	90.6	3.6	23.5	90.6	3.6
120	90	240	20.3	80.8	3.0	20.3	80.8	3.0	20.3	80.8	3.0
120	90	250	17.1	70.9	2.4	17.1	70.9	2.4	17.1	70.9	2.4
120	90	260	13.9	61.0	1.8	13.9	61.0	1.8	13.9	61.0	1.8
120	90	270	10.7	51.1	1.2	10.7	51.1	1.2	10.7	51.1	1.2
120	90	280	7.5	41.2	0.6	7.5	41.2	0.6	7.5	41.2	0.6
120	90	290	4.3	31.3	0.0	4.3	31.3	0.0	4.3	31.3	0.0
120	90	300	1.1	21.4	-0.6	1.1	21.4	-0.6	1.1	21.4	-0.6

[illegible]

Refer to air tables in back of this crane catalog for additional details regarding the capacities.

14 Columns

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	Boom Angle (deg)	Jib Height (ft)	SWL Capacity (1000 lbs)	SWL Angle (deg)	Jib Height (ft)	SWL Capacity (1000 lbs)	SWL Angle (deg)	Jib Height (ft)	SWL Capacity (1000 lbs)	SWL Angle (deg)	Jib Height (ft)	SWL Capacity (1000 lbs)	SWL Angle (deg)
100	30	110	37.3	85.8	38.5	36.4	84.2	54.4							
100	30	120	29.1	85.8	32.3										
100	50	30	81.5	157.2	32.5										
100	50	35	79.5	158.2	32.5										
100	50	40	77.5	158.1	32.5										
100	50	50	73.7	152.2	32.5	85.8	156.5	31.7	76.8	148.5	29.3				
100	50	60	69.7	148.5	31.4	72.5	147.5	29.5	75.8	145.3	28.5				
100	50	70	65.8	144.1	30.4	68.7	143.5	28.1	71.5	140.7	27.9				
100	50	80	61.5	138.5	29.4	64.4	137.5	26.3	67.5	135.2	25.9				
100	50	90	56.9	132.4	28.5	59.8	131.2	25.7	62.5	128.7	25.3				
100	50	100	52.2	126.8	28.3	55.1	123.5	23.5	57.7	120.8	19.5				
100	50	110	47.1	115.8	25.5	50.5	114.4	21.7	52.4	111.5	17.5				
100	50	120	41.5	105.0	23.5	44.3	103.4	20.2	46.6	100.1					
100	50	130	35.2	91.5	21.7	37.9	89.7	19.1							
100	50	140	27.7	74.1	20.2										
100	70	35	81.4	176.6	21.9										
100	70	40	78.7	175.6	21.6										
100	70	50	76.3	173.1	21.1	80.2	171.7	20.1	80.4	165.9	18.2				
100	70	60	72.8	169.9	20.6	76.7	168.6	19.4	76.7	161.9	17.2				
100	70	70	69.2	166.1	19.9	73.1	164.7	18.7	73.0	157.2	15.7				
100	70	80	65.5	161.5	19.2	69.4	160.1	18.0	69.1	151.7	14.5				
100	70	90	61.8	156.1	18.4	65.6	154.6	17.4	65.0	145.2	13.5				
100	70	100	57.8	149.8	17.8	61.6	148.2	16.8	60.8	137.6	12.6				
100	70	110	53.7	142.4	17.1	57.4	140.6	16.0	56.2	128.7	11.9				
100	70	120	49.3	133.9	16.4	53.0	132.1	14.6	51.3	118.2	11.2				
100	70	130	44.6	123.9	15.7	48.2	122.0	13.6	45.8	105.6	10.7				
100	70	140	39.4	111.9	14.9	42.9	109.8	12.8							
100	70	150	33.6	97.4	14.1	36.9	94.9	12.2							
100	70	160	26.5	78.5	13.3										
100	90	40	81.3	196.0	13.8										
100	90	50	78.2	193.7	13.4										
100	90	60	75.1	190.9	12.9	79.7	189.4	12.0	80.8	182.9	10.4				
100	90	70	72.0	187.5	12.4	76.5	186.0	11.4	77.5	178.7	10.1				
100	90	80	68.8	183.5	11.8	73.3	181.9	10.7	74.2	173.9	9.9				
100	90	90	65.5	178.8	11.1	69.9	177.2	10.3	70.7	168.3	9.7				
100	90	100	62.1	173.4	10.5	66.5	171.7	10.1	67.0	161.8	9.4				
100	90	110	58.6	167.1	10.2	63.0	165.4	9.8	63.2	154.4	8.9				
100	90	120	54.9	159.9	10.0	59.2	158.1	9.6	59.2	145.9	8.4				
100	90	130	51.1	151.7	9.7	55.3	149.8	9.3	54.9	136.0	7.9				
100	90	140	47.0	142.3	9.4	51.2	140.2	9.0	50.3	124.5	7.5				
100	90	150	42.5	131.4	9.1	46.7	129.1	8.6	45.1	110.7	7.2				
100	90	160	37.7	118.5	8.7	41.7	115.9	8.1							
100	90	170	32.1	102.8	8.2	36.0	99.8	7.6							
100	90	180	25.4	82.7	7.5										
110	30	30	80.2	147.1	40.0	80.2	145.3	40.0	80.0	142.5	40.0				
110	30	35	78.1	146.0	40.0	78.1	144.0	40.0	75.7	139.4	40.0				
110	30	40	76.1	144.8	40.0	73.8	140.9	40.0	71.3	135.4	39.1				
110	30	50	71.8	141.7	40.0	69.5	137.0	40.0							
110	30	60	67.5	137.8	40.0										

Refer to all notes in back of this Crane Rating Manual before operating this machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	Jib Angle to Radius			Jib Angle to Radius			Jib Angle to Radius		
			Boom Angle (deg)	Jib Height (ft)	ABA Capacity (tons) (ft)	Boom Angle (deg)	Jib Height (ft)	ABA Capacity (tons) (ft)	Boom Angle (deg)	Jib Height (ft)	ABA Capacity (tons) (ft)
80	30	100	51.8	82.2	35.3 *						
80	50	30	80.2	138.8	32.0 *						
80	50	35	78.0	135.7	32.0 *						
80	50	40	75.7	132.4	32.0 *	81.6	134.7	31.8 *			
80	50	45	73.2	129.0	31.7 *	79.4	131.4	31.5 *			
80	50	50	71.2	125.8	30.8 *	74.8	125.0	30.5 *	78.5	128.0	28.1 *
80	50	55	68.4	121.5	29.6 *	70.0	120.4	28.2 *	73.4	123.5	24.8 *
80	50	60	65.5	115.0	28.8 *	65.1	120.4	28.7 *	68.3	118.2	22.4 *
80	50	65	62.4	107.1	27.9 *	59.8	113.8	25.7 *	63.0	111.5	20.5 *
80	50	70	59.0	97.4	24.9 *	54.3	105.8	23.2 *	57.3	103.3	18.9 *
80	50	75	55.8	88.8	22.5 *	48.2	98.0	21.2 *	51.0	93.2	17.8 *
80	50	80	52.9	80.4	20.6 *	41.2	83.7	19.8 *			
80	70	35	80.2	156.2	21.7 *						
80	70	40	78.3	153.0	21.4 *						
80	70	45	74.4	152.2	20.8 *	78.8	151.0	19.8 *	79.0	144.8	18.0 *
80	70	50	70.4	148.6	20.1 *	74.8	147.3	19.0 *	74.8	140.3	16.4 *
80	70	55	66.3	144.1	19.3 *	70.6	142.8	18.2 *	70.4	134.8	14.9 *
80	70	60	62.0	138.8	18.4 *	66.3	137.4	16.8 *	65.8	128.2	13.7 *
80	70	65	57.5	132.4	17.7 *	61.8	131.0	15.7 *	60.9	120.3	12.7 *
80	70	70	52.8	124.8	17.0 *	57.0	123.3	14.4 *	55.6	110.9	11.8 *
80	70	75	47.7	115.8	16.2 *	51.9	114.2	13.4 *	49.7	99.5	11.1 *
80	70	80	42.2	104.9	15.3 *	46.3	103.1	12.5 *			
80	70	85	35.9	91.6	14.5 *	39.8	89.5				
80	70	90	28.3	74.1	13.5 *						
80	90	35	82.0	176.6	13.9 *						
80	90	40	80.3	175.6	13.7 *						
80	90	45	76.8	173.1	13.2 *	81.9	171.7	12.4 *			
80	90	50	73.3	169.9	12.7 *	78.4	168.5	11.7 *			
80	90	55	69.8	166.1	12.0 *	74.8	164.6	11.0 *	79.7	161.8	10.3 *
80	90	60	66.1	161.5	11.3 *	71.1	160.0	10.4 *	75.9	157.1	10.0 *
80	90	65	62.3	156.1	10.5 *	67.3	154.5	10.1 *	72.0	151.5	9.8 *
80	90	70	58.4	149.8	10.2 *	63.3	148.2	9.9 *	67.9	145.0	9.5 *
80	90	75	54.3	142.4	9.9 *	59.2	140.7	9.6 *	63.7	137.4	9.0 *
80	90	80	49.9	133.9	9.6 *	54.7	132.1	9.3 *	59.1	128.5	8.4 *
80	90	85	45.2	123.8	9.3 *	49.9	121.9	8.9 *	54.2	118.0	7.9 *
80	90	90	40.0	111.9	9.0 *	44.7	109.8	8.4 *	48.7	105.3	7.5 *
80	90	95	34.1	97.4	8.4 *	38.6	94.8	7.8 *			
80	90	100	27.0	78.5	7.7 *						
90	30	25	80.9	127.7	40.0 *	80.9	125.9	40.0 *			
90	30	30	78.6	126.6	40.0 *	78.5	124.7	40.0 *	80.7	123.3	40.0 *
90	30	35	76.1	125.4	40.0 *	76.0	123.2	40.0 *	78.2	121.8	40.0 *
90	30	40	73.7	123.9	40.0 *	71.0	119.6	40.0 *	73.1	118.1	40.0 *
90	30	45	68.7	120.3	40.0 *	65.8	114.8	40.0 *	67.9	113.3	36.7 *
90	30	50	63.5	115.6	40.0 *	60.3	108.9	40.0 *	62.3	107.3	36.8 *
90	30	55	58.1	109.8	40.0 *	54.5	101.6	37.1 *	56.3	99.8	34.8 *
90	30	60	52.3	102.5	40.0 *	48.1	92.5	36.8 *	49.8	90.5	32.3 *
90	30	65	46.0	93.5	38.1 *	40.9	80.9	35.0 *			
90	30	70	38.9	82.0	36.9 *						
90	30	75	30.4	66.9	34.8 *						


His Angle to Bloom

28p1131

Factor to all values in table of this column. Rating. Material factors representing the structure.											
Room Length (ft)	Room Width (ft)	Room Height (ft)	Room Area (sq ft)	Room Volume (cu ft)	Room Capacity (people)	Room Area (sq ft)	Room Volume (cu ft)	Room Capacity (people)	Room Area (sq ft)	Room Volume (cu ft)	Room Capacity (people)
60	30	15	1800	27000	100	1800	27000	100	1800	27000	100
60	30	20	1800	36000	133	1800	36000	133	1800	36000	133
60	30	25	1800	45000	167	1800	45000	167	1800	45000	167
60	30	30	1800	54000	200	1800	54000	200	1800	54000	200
60	30	35	1800	63000	233	1800	63000	233	1800	63000	233
60	30	40	1800	72000	267	1800	72000	267	1800	72000	267
60	30	45	1800	81000	300	1800	81000	300	1800	81000	300
60	30	50	1800	90000	333	1800	90000	333	1800	90000	333
60	30	55	1800	99000	367	1800	99000	367	1800	99000	367
60	30	60	1800	108000	400	1800	108000	400	1800	108000	400
60	30	65	1800	117000	433	1800	117000	433	1800	117000	433
60	30	70	1800	126000	467	1800	126000	467	1800	126000	467
60	30	75	1800	135000	500	1800	135000	500	1800	135000	500
60	30	80	1800	144000	533	1800	144000	533	1800	144000	533
60	30	85	1800	153000	567	1800	153000	567	1800	153000	567
60	30	90	1800	162000	600	1800	162000	600	1800	162000	600
60	30	95	1800	171000	633	1800	171000	633	1800	171000	633
60	30	100	1800	180000	667	1800	180000	667	1800	180000	667
60	30	105	1800	189000	700	1800	189000	700	1800	189000	700
60	30	110	1800	198000	733	1800	198000	733	1800	198000	733
60	30	115	1800	207000	767	1800	207000	767	1800	207000	767
60	30	120	1800	216000	800	1800	216000	800	1800	216000	800
60	30	125	1800	225000	833	1800	225000	833	1800	225000	833
60	30	130	1800	234000	867	1800	234000	867	1800	234000	867
60	30	135	1800	243000	900	1800	243000	900	1800	243000	900
60	30	140	1800	252000	933	1800	252000	933	1800	252000	933
60	30	145	1800	261000	967	1800	261000	967	1800	261000	967
60	30	150	1800	270000	1000	1800	270000	1000	1800	270000	1000
60	30	155	1800	279000	1033	1800	279000	1033	1800	279000	1033
60	30	160	1800	288000	1067	1800	288000	1067	1800	288000	1067
60	30	165	1800	297000	1100	1800	297000	1100	1800	297000	1100
60	30	170	1800	306000	1133	1800	306000	1133	1800	306000	1133
60	30	175	1800	315000	1167	1800	315000	1167	1800	315000	1167
60	30	180	1800	324000	1200	1800	324000	1200	1800	324000	1200
60	30	185	1800	333000	1233	1800	333000	1233	1800	333000	1233
60	30	190	1800	342000	1267	1800	342000	1267	1800	342000	1267
60	30	195	1800	351000	1300	1800	351000	1300	1800	351000	1300
60	30	200	1800	360000	1333	1800	360000	1333	1800	360000	1333
60	30	205	1800	369000	1367	1800	369000	1367	1800	369000	1367
60	30	210	1800	378000	1400	1800	378000	1400	1800	378000	1400
60	30	215	1800	387000	1433	1800	387000	1433	1800	387000	1433
60	30	220	1800	396000	1467	1800	396000	1467	1800	396000	1467
60	30	225	1800	405000	1500	1800	405000	1500	1800	405000	1500
60	30	230	1800	414000	1533	1800	414000	1533	1800	414000	1533
60	30	235	1800	423000	1567	1800	423000	1567	1800	423000	1567
60	30	240	1800	432000	1600	1800	432000	1600	1800	432000	1600
60	30	245	1800	441000	1633	1800	441000	1633	1800	441000	1633
60	30	250	1800	450000	1667	1800	450000	1667	1800	450000	1667
60	30	255	1800	459000	1700	1800	459000	1700	1800	459000	1700
60	30	260	1800	468000	1733	1800	468000	1733	1800	468000	1733
60	30	265	1800	477000	1767	1800	477000	1767	1800	477000	1767
60	30	270	1800	486000	1800	1800	486000	1800	1800	486000	1800
60	30	275	1800	495000	1833	1800	495000	1833	1800	495000	1833
60	30	280	1800	504000	1867	1800	504000	1867	1800	504000	1867
60	30	285	1800	513000	1900	1800	513000	1900	1800	513000	1900
60	30	290	1800	522000	1933	1800	522000	1933	1800	522000	1933
60	30	295	1800	531000	1967	1800	531000	1967	1800	531000	1967
60	30	300	1800	540000	2000	1800	540000	2000	1800	540000	2000
60	30	305	1800	549000	2033	1800	549000	2033	1800	549000	2033
60	30	310	1800	558000	2067	1800	558000	2067	1800	558000	2067
60	30	315	1800	567000	2100	1800	567000	2100	1800	567000	2100
60	30	320	1800	576000	2133	1800	576000	2133	1800	576000	2133
60	30	325	1800	585000	2167	1800	585000	2167	1800	585000	2167
60	30	330	1800	594000	2200	1800	594000	2200	1800	594000	2200
60	30	335	1800	603000	2233	1800	603000	2233	1800	603000	2233
60	30	340	1800	612000	2267	1800	612000	2267	1800	612000	2267
60	30	345	1800	621000	2300	1800	621000	2300	1800	621000	2300
60	30	350	1800	630000	2333	1800	630000	2333	1800	630000	2333
60	30	355	1800	639000	2367	1800	639000	2367	1800	639000	2367
60	30	360	1800	648000	2400	1800	648000	2400	1800	648000	2400
60	30	365	1800	657000	2433	1800	657000	2433	1800	657000	2433
60	30	370	1800	666000	2467	1800	666000	2467	1800	666000	2467
60	30	375	1800	675000	2500	1800	675000	2500	1800	675000	2500
60	30	380	1800	684000	2533	1800	684000	2533	1800	684000	2533
60	30	385	1800	693000	2567	1800	693000	2567	1800	693000	2567
60	30	390	1800	702000	2600	1800	702000	2600	1800	702000	2600
60	30	395	1800	711000	2633	1800	711000	2633	1800	711000	2633
60	30	400	1800	720000	2667	1800	720000	2667	1800	720000	2667
60	30	405	1800	729000	2700	1800	729000	2700	1800	729000	2700
60	30	410	1800	738000	2733	1800	738000	2733	1800	738000	2733
60	30	415	1800	747000	2767	1800	747000	2767	1800	747000	2767
60	30	420	1800	756000	2800	1800	756000	2800	1800	756000	2800
60	30	425	1800	765000	2833	1800	765000	2833	1800	765000	2833
60	30	430	1800	774000	2867	1800	774000	2867	1800	774000	2867
60	30	435	1800	783000	2900	1800	783000	2900	1800	783000	2900
60	30	440	1800	792000	2933	1800	792000	2933	1800	792000	2933
60	30	445	1800	801000	2967	1800	801000	2967	1800	801000	2967
60	30	450	1800	810000	3000	1800	810000	3000	1800	810000	3000
60	30	455	1800	819000	3033	1800	819000	3033	1800	819000	3033
60	30	460	1800	828000	3067	1800	828000	3067	1800	828000	3067
60	30	465	1800	837000	3100	1800	837000	3100	1800	837000	3100
60	30	470	1800	846000	3133	1800	846000	3133	1800	846000	3133
60	30	475	1800	855000	3167	1800	855000	3167	1800	855000	3167
60	30	480	1800	864000	3200	1800	864000	3200	1800	864000	3200
60	30	485	1800	873000	3233	1800	873000	3233	1800	873000	3233
60	30	490	1800	882000	3267	1800	882000	3267	1800	882000	3267
60	30	495	1800	891000	3300	1800	891000	3300	1800	891000	3300
60	30	500	1800	900000	3333	1800	900000	3333	1800	900000	3333
60	30	505	1800	909000	3367	1800	909000	3367	1800	909000	3367
60	30	510	1800	918000	3400	1800	918000	3400	1800	918000	3400
60	30	515	1800	927000	3433	1800	927000	3433	1800	927000	3433
60	30	520	1800	936000	3467	1800	936000	3467	1800	936000	3467
60	30	525	1800	945000	3500	1800	945000	3500	1800	945000	3500
60	30	530	1800	954000	3533	1800	954000	3533	1800	954000	3533
60	30	535	1800	963000	3567	1800	963000	3567	1800	963000	3567
60	30	540	1800	972000	3600	1800	972000	3600	1800	972000	3600
60	30	545	1800	981000	3633	1800	981000	3633	1800	981000	3633
60	30	550	1800								

WORKING RANGE DIAGRAM

50' TO 330' (15.25 m TO 91.44 m) MAIN BOOM + 50' (27.4 m) MAX. JIB



Notes:

1. Boom geometry shown is for unloaded condition and crane standing level on firm supporting surface. Boom deflection, subsequent radius and boom angle change must be accounted for when applying load to hook.
2. Maximum and minimum boom angles are equal to the values listed in the capacity chart for each boom length.

Working Range Diagram

CD01770

ON TIRE
CAPACITIES



**Main Boom Capacities (Kips) – On Tires – Centered Over The Rear
200 Ft (61.0 m) Open Throat Tube Boom**


Boom Capacities (Kips) - On Tires - Centered Over The Rear 200 Ft (61.0 m) Open Throat Tube Boom						
Load Radius (ft)	Boom Angle (deg)	Counterweight Combinations				Load Radius (ft)
		Static		Dynamic (1.6 km/h)		
		AB	A+A	AB	A+A	
32	81.7	64.3		64.3		32
35	80.8	57.4		57.4		35
40	79.4	48.3		48.3		40
50	76.5	36.4		36.4		50
60	73.5	28.3		28.3		60
70	70.5	22.5		22.5		70
80	67.4	18.3		18.3		80
90	64.3	15.0		15.0		90
100	61.0	12.4		12.4		100
110	57.7	10.3		10.3		110
120	54.3	8.6		8.6		120
130	50.6	7.1		7.1		130
140	46.8	5.8		5.8		140
150	42.8	4.7		4.7		150
160	38.4	3.8		3.8		160
170	33.5	3.0		3.0		170
180	27.9	2.2		2.2		180
190	20.9	-		-		190
200	10.2	-		-		200

PROHIBITED

PROHIBITED

Note: Refer To Page 14 For "Capacity Deductions" Caused By Any Jib Attachment.

Note: Refer To Page 14 For "Capacity Deductions" Caused By Any Jib Attachment.




**Main Boom Capacities (Kips) – On Tires – Centered Over The Rear
190 Ft (57.9 m) Open Throat Tube Boom**

Counterweight Combinations						
Load Radius (ft)	Boom Angle (deg)	Static		Dynamic (1.6 km/h)		Load Radius (ft)
		AB	A+A	AB	A+A	
30	81.9	70.1	PROHIBITED	70.1	PROHIBITED	30
35	80.4	57.7		57.7		35
40	78.8	48.7		48.7		40
50	75.7	36.2		36.2		50
60	72.6	28.6		28.6		60
70	69.4	22.9		22.9		70
80	66.1	18.6		18.6		80
90	62.8	15.4		15.4		90
100	59.4	12.8		12.8		100
110	55.8	10.7		10.7		110
120	52.1	8.9		8.9		120
130	48.1	7.4		7.4		130
140	43.9	6.2		6.2		140
150	39.4	5.1		5.1		150
160	34.4	4.1		4.1		160
170	28.6	3.3		3.3		170
180	21.5	2.6		2.6		180
190	10.5	1.9		1.9		190

Note: Refer To Page 14 For "Capacity Deductions" Caused By Any Jib Attachment.

ON TIRE CAPACITIES



**Main Boom Capacities (Kips) – On Tires – Centered Over The Rear
180 Ft (54.9 m) Open Throat Tube Boom**

Boom Capacities (Kips) — On Tires — Centered Over The Rear 180 Ft (54.9 m) Open Throat Tube Boom						
Load Radius (ft)	Boom Angle (deg)	Counterweight Combinations				Load Radius (ft)
		Static		Dynamic (1.6 km/h)		
		AB	A+A	AB	A+A	
29	81.7	73.0	63.0	73.0	63.0	29
30	81.4	70.4	60.3	70.4	60.3	30
35	79.8	58.1	49.5	58.1	49.5	35
40	78.2	49.0	41.6	49.0	41.6	40
50	74.9	36.6	31.2	36.6	31.2	50
60	71.6	28.9	24.1	28.9	24.1	60
70	68.2	23.2	19.1	23.2	19.1	70
80	64.7	19.0	15.4	19.0	15.4	80
90	61.2	15.7	12.5	15.7	12.5	90
100	57.5	13.1	10.3	13.1	10.3	100
110	53.6	11.0	8.4	11.0	8.4	110
120	49.5	9.3	6.9	9.3	6.9	120
130	45.2	7.8	5.6	7.8	5.6	130
140	40.5	6.5	4.5	6.5	4.5	140
150	35.3	5.4	3.5	5.4	3.5	150
160	29.4	4.5	2.7	4.5	2.7	160
170	22.1	3.6	2.0	3.6	2.0	170
180	10.8	2.9	—	2.9	—	180

Refer To Page 14 For "Capacity Deductions" Caused By Any Jib Attachment.

Refer To Page 14 For "Capacity Deductions" Caused By Any Jib Attachment.



**Main Boom Capacities (Kips) – On Tires – Centered Over The Rear
170 Ft (51.8 m) Open Throat Tube Boom**

Load Radius (ft)	Boom Angle (deg)	Counterweight Combinations				Load Radius (ft)
		Static		Dynamic (1.6 km/h)		
		AB	A+A	AB	A+A	
27	81.9	80.2	69.2	80.2	69.2	27
30	80.9	70.8	60.6	70.8	60.6	30
35	79.2	58.4	49.8	58.4	49.8	35
40	77.5	49.3	41.9	49.3	41.9	40
50	74.0	36.9	31.5	36.9	31.5	50
60	70.5	29.2	24.4	29.2	24.4	60
70	66.9	23.5	19.4	23.5	19.4	70
80	63.1	19.3	15.7	19.3	15.7	80
90	59.3	16.0	12.9	16.0	12.9	90
100	55.3	13.4	10.6	13.4	10.6	100
110	51.1	11.3	8.7	11.3	8.7	110
120	46.6	9.6	7.2	9.6	7.2	120
130	41.7	8.1	5.9	8.1	5.9	130
140	36.4	6.8	4.8	6.8	4.8	140
150	30.3	5.7	3.9	5.7	3.9	150
160	22.7	4.8	3.0	4.8	3.0	160
170	11.1	3.9	2.3	3.9	2.3	170

Note: Refer To Page 14 For "Capacity Deductions" Caused By Any Jib Attachment.

JIB CAPACITIES

9/24/2017

Load Chart

Project
Customer
Description

Link-Belt HC-268

Boom: Open Throat Main Boom
Jib: 50' Tubular Jib
Base: On Outriggers w/ Front Center Jack
Counterweight: 85,000 lbs AB + 26,700 lbs AB Bumper
Range: 360°
Capacity: 85% Cap
Chart ID:

Boom Length (ft)	Boom Angle	Jib Length (ft)	Jib Offset	Tip Height (ft)	Lift Radius (ft)	Capacity (lbs)	Note
240	81.9°	50	5°	294.7	50	32,000	
240	79.9°	50	5°	292.9	60	32,000	
240	77.9°	50	5°	290.8	70	32,000	
240	75.9°	50	5°	288.3	80	31,600	
240	73.8°	50	5°	285.4	90	29,600	
240	71.7°	50	5°	282.1	100	27,800	
240	69.6°	50	5°	278.4	110	26,100	
240	67.5°	50	5°	274.2	120	24,500	
240	65.3°	50	5°	269.7	130	23,000	
240	63.1°	50	5°	264.6	140	21,700	
240	60.9°	50	5°	259.1	150	19,400	
240	58.6°	50	5°	253	160	17,200	
240	56.2°	50	5°	246.4	170	15,200	
240	53.8°	50	5°	239.1	180	13,600	
240	51.3°	50	5°	231.1	190	12,000	
240	48.7°	50	5°	222.4	200	10,700	
240	45.9°	50	5°	212.9	210	9,500	
240	43.1°	50	5°	202.3	220	8,400	
240	40.1°	50	5°	190.7	230	7,400	
240	36.8°	50	5°	177.6	240	6,500	
240	33.3°	50	5°	162.8	250	5,700	
240	29.4°	50	5°	145.7	260	4,900	

data is for reference use only. Operator must refer to in-cab charts to determine allowable lifting capacities.

Refer to all notes in front of the Crane Rating Manual before operating the machine.

Boom Length (ft)	Jib Length (ft)	Jib Load Radius (ft)	Boom Angle (deg)	4 Degrees		16 Degrees		28 Degrees	
				Jib Pt Height (ft)	AB+AB Capacity (1000 lbs)	Jib Pt Height (ft)	AB+AB Capacity (1000 lbs)	Jib Pt Height (ft)	AB+AB Capacity (1000 lbs)
280	70	120	72.1	350.1	15.5 *	74.0	345.3	13.3 *	75.7
280	70	130	70.5	348.6	13.9 *	72.3	344.7	12.0 *	73.9
280	70	140	68.8	347.7	12.6 *	70.8	343.5	10.9 *	72.2
280	70	150	67.0	346.8	11.1 *	69.1	342.5	10.0 *	70.5
280	70	160	65.3	345.8	10.8 *	67.1	341.9	9.1 *	68.7
280	70	170	63.5	344.8	9.2 *	65.3	341.4	8.3 *	66.9
280	70	180	61.7	343.8	7.7 *	63.5	340.3	6.9 *	65.1
280	70	190	59.9	342.4	6.6 *	61.7	339.3	6.4 *	63.2
280	70	200	58.0	341.3	5.7	59.9	338.5	5.9 *	61.3
280	70	210	56.1	340.6	4.8	58.1	337.5	5.4 *	59.4
280	70	220	54.2	339.4	4.0	56.3	336.5	5.1 *	57.4
280	70	230	52.2	338.6	3.3	54.5	335.5	4.7 *	55.3
280	70	240	50.1	337.7	2.6	52.7	334.5	4.3 *	53.2
280	70	250	48.0	336.8	2.0	50.9	333.5	4.0 *	51.0
280	70	260	45.8	335.8	1.3	49.1	332.5	3.7	48.8
280	70	270	43.5	334.8	0.8	47.3	331.5	3.0	46.4
280	70	280	41.1	333.9	0.2	45.5	330.5	2.3	44.6
280	70	290	38.6	332.9	0.0	43.7	329.5	1.8	42.8
280	80	80	81.1	383.6	13.8 *	81.9	379.5	12.4 *	80.9
280	80	90	79.6	381.6	13.6 *	80.3	377.3	12.1 *	79.3
280	80	100	78.0	379.5	13.4 *	78.8	374.8	11.8 *	77.7
280	80	110	76.5	377.0	13.1 *	77.2	372.0	11.2 *	76.1
280	80	120	74.9	374.2	12.9 *	75.6	369.0	10.2 *	74.5
280	80	130	73.4	371.1	12.0 *	74.0	365.6	9.1 *	72.8
280	80	140	71.8	367.8	11.1 *	72.4	361.9	8.3 *	71.1
280	80	150	70.2	364.1	10.2 *	70.8	357.8	7.6 *	69.5
280	80	160	68.6	360.1	9.4 *	69.1	353.5	6.8 *	67.7
280	80	170	66.9	355.8	8.5 *	67.5	348.8	6.3 *	66.0
280	80	180	65.3	351.1	7.9 *	65.8	343.7	5.6 *	64.2
280	80	190	63.6	346.1	7.2 *	64.1	338.3	5.1 *	62.4
280	80	200	61.9	340.7	6.6 *	62.3	332.4	4.7 *	60.6
280	80	210	60.2	334.9	6.1 *	60.5	326.1	4.4 *	58.7
280	80	220	58.4	328.6	5.6 *	58.7	319.4	4.0 *	56.9
280	80	230	56.6	322.0	5.2 *	57.0	312.2	3.7 *	55.0
280	80	240	54.8	314.8	4.8 *	55.0	304.5	3.4 *	53.0
280	80	250	52.9	307.2	4.5 *	53.0	296.3	3.1 *	51.0
280	80	260	50.9	299.0	4.1 *	50.9	287.4	2.9 *	48.9
280	80	270	48.9	290.3	3.9 *	48.9	277.9	2.7 *	46.8
280	80	280	46.9	280.9	3.5 *	46.8	267.7	2.5 *	44.5
280	80	290	44.8	270.7	3.0	44.5	256.6	2.4 *	42.4
280	90	30	42.5	259.8	2.4	42.4	245.5	2.3 *	40.3
300	30	60	80.6	334.7	33.5 *	81.5	333.9	32.3 *	80.5
300	30	70	78.8	332.8	30.9 *	79.7	332.0	29.7 *	78.7
300	30	80	77.1	330.6	28.4 *	77.9	329.8	27.1 *	76.9
300	30	90	75.3	328.1	26.1 *	76.2	327.2	24.8 *	75.1
300	30	100	73.5	325.2	24.0 *	74.4	324.3	22.7 *	73.3
300	30	110	71.7	322.0	21.9 *	72.5	321.1	20.8 *	71.5
300	30	120	69.9	318.4	20.1 *	70.7	317.5	19.2 *	69.6
300	30	130	68.0	314.4	18.5 *	68.8	313.6	17.6 *	67.7
300	30	140	66.1	310.1	17.0 *	67.0	309.2	16.1 *	65.8
300	30	150	64.2	305.4	15.6 *	65.0	304.5	14.8 *	63.9
300	30	160							
300	30	170							
300	30	180							
300	30	190							
300	30	200							
300	30	210							
300	30	220							
300	30	230							
300	30	240							
300	30	250							
300	30	260							
300	30	270							
300	30	280							
300	30	290							
300	30	300							
300	30	310							
300	30	320							
300	30	330							
300	30	340							
300	30	350							
300	30	360							
300	30	370							
300	30	380							
300	30	390							
300	30	400							
300	30	410							
300	30	420							
300	30	430							
300	30	440							
300	30	450							
300	30	460							
300	30	470							
300	30	480							
300	30	490							
300	30	500							
300	30	510							
300	30	520							
300	30	530							
300	30	540							
300	30	550							
300	30	560							
300	30	570							
300	30	580							
300	30	590							
300	30	600							
300	30	610							
300	30	620							
300	30	630							
300	30	640							
300	30	650							
300	30	660							
300	30	670							
300	30	680							
300	30	690							
300	30	700							
300	30	710							
300	30	720							
300	30	730							
300	30	740							
300	30	750							
300	30	760							
300	30	770							
300	30	780							
300	30	790							
300	30	800							
300	30	810							
300	30	820							
300	30	830							
300	30	840							
300	30	850							
300	30	860							
300	30	870							
300	30	880							
300	30	890							
300	30	900							
300	30	910							
300	30	920							
300	30	930							
300	30	940							
300	30	950							
300	30	960							
300	30	970							
300	30	980							
300	30	990							
300	30	1000							